



## Support Grips

**Heavy Duty Support**

Single Eye, Double Weave, Tin-Coated Bronze

**IMPORTANT!**

It is important that you read all breaking strength, safety and technical data relating to this product on pages T-43 through T-48.

**Heavy Duty, Single Eye, Closed Mesh****Single Eye, Split Mesh, Lace Closing****Heavy Duty, Single Eye, Closed Mesh\***

For heavy duty permanent support when cable end is available to be installed through grip.

Cable Diameter Range Inches (cm)	Approx. Breaking Strength Lbs. (N)	E Inches (cm)	M Inches (cm)	Catalog Numbers
.75"- .99" (1.90-2.51)	2,820 (12,543)	10" (25.40)	25" (63.50)	<b>02206010</b>
1.00"-1.24" (2.54-3.15)	4,280 (19,037)	12" (30.48)	28" (71.12)	<b>02206011</b>
1.25"-1.49" (3.17-3.78)	4,280 (19,037)	12" (30.48)	30" (76.20)	<b>02206012</b>
1.50"-1.99" (3.81-5.05)	4,280 (19,037)	12" (30.48)	34" (86.36)	<b>02206013</b>

**Single Eye, Split Mesh, Lace Closing\***

For permanent support when cable end is not available to be installed through grip.

Cable Diameter Range Inches (cm)	Approx. Breaking Strength Lbs. (N)	E Inches (cm)	M Inches (cm)	Catalog Numbers
.75"- .99" (1.90-2.51)	2,820 (12,543)	10" (25.40)	25" (63.50)	<b>02207010</b>
1.00"-1.24" (2.54-3.15)	4,280 (19,037)	12" (30.48)	28" (71.12)	<b>02207011</b>
1.25"-1.49" (3.17-3.78)	4,280 (19,037)	12" (30.48)	30" (76.20)	<b>02207012</b>
1.50"-1.99" (3.81-5.05)	4,280 (19,037)	12" (30.48)	34" (86.36)	<b>02207013</b>

*E-Eye length*

*M-Mesh length at nominal diameter*

\* Change catalog number from 022 to 024 for stainless steel. Consult factory for availability.