

SAK Series
QL 10 SAK2.5**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Product image**

Similar to illustration

Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| | |
|------------|---|
| Type | QL 10 SAK2.5 |
| Order No. | 0338 100000 |
| Version | SAK Series, Cross-connector, for cross-connection link, Number of poles: 10 |
| GTIN (EAN) | 4008 190189426 |
| Qty. | 20 pc(s). |

Creation date August 21, 2020 6:38:16 PM CEST

Catalogue status 14.08.2020 / We reserve the right to make technical changes.

Data sheet

**SAK Series
QL 10 SAK2.5**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Width | 60.6 mm | Width (inches) | 2.386 inch |
| Height | 6 mm | Height (inches) | 0.236 inch |
| Depth | 0.6 mm | Depth (inches) | 0.024 inch |
| Net weight | 1.55 g | | |

Temperatures

| | | | |
|---------------------------|----------------|---------------------------|--------|
| Storage temperature, max. | 55 °C | Storage temperature, min. | -25 °C |
| Storage temperature | -25 °C...55 °C | | |

Material data

| | | | |
|----------|--------|--------|------|
| Material | Copper | Colour | grey |
|----------|--------|--------|------|

System specifications

| | |
|---------|---------------------------|
| Version | for cross-connection link |
|---------|---------------------------|

Additional technical data

| | | | |
|--------------------------|-----------------|---------------------|-----------------|
| Explosion-tested version | No | Installation advice | Direct mounting |
| Type of fixing | when screwed in | | |

Dimensions

| | |
|-----------------|------|
| Pitch in mm (P) | 6 mm |
|-----------------|------|


Rating data

| | |
|---------------|------|
| Rated current | 32 A |
|---------------|------|

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC000489 | ETIM 7.0 | EC000489 |
| eClass 9.0 | 27-14-11-40 | eClass 9.1 | 27-14-11-40 |
| eClass 10.0 | 27-14-11-40 | UNSPSC | 30-21-18-01 |

Approvals

| | |
|-----------|---|
| Approvals |  |
|-----------|---|

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|---|---|
| Approval/Certificate/Document of Conformity | EAC certificate |
| Engineering Data | EPLAN, WSCAD |
| User Documentation | StorageConditionsTerminalBlocks |