




Circular connectors with threaded joint M16 acc. to IEC 61076-2-106, IP40/IP68




Slit nut for chassis plugs and sockets (spare part)









Environmental conditions

Temperature range

-40 °C/+85 °C

1-3 Nm

Mechanical data

Tightening torque nut

Associated products

| Accessories | | |
|-------------|-----------------------|-------------------------|
| ☑ 030398 | ☑ 0304 | C 0304-1 |
| ☑ 0304-2 | ☑ 0305 | C 0305-1 |
| 🗗 0305-1 U | ☑ 0305-2 | 1 0306 |
| C 0306-1 | ☑ 0306-2 | 1 0307 |
| ☑ 0307-1 | ☑ 0307-2 | L ^a 030798-1 |
| ☑ 030798-2 | ☞ 030799-2 | C 0314 |
| ☑ 0314-1 | C 0314-2 | C [*] 0315 |
| C 0315-1 | 🗗 0315-1 U | C [*] 0315-2 |
| C 0316 | C 0316-1 | C 0316-2 |
| C 0317 | C [*] 0317-1 | C [*] 0317-2 |
| C 031798-1 | C 031798-2 | C 031799-2 |
| C 0362 | C 0363 | 🗗 KFR |
| C∕r KFV | 🗗 KGR | 🖻 KGV |
| I SFV | 🖸 SGR | 🖻 SGV |
| | | |





| Designation | Pole Number | PU (Pieces) | MDQ (Pieces) |
|-------------|-------------|-------------|--------------|
| 0385 | - | 100 | 500 |

Packaging: in a cardboard box

3 of 3