
### Terminal markers DEK 5 FS 101-150



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com



The **dekafix (DEK)** marker is the universal marker for all conductor and plug-in connectors as well as for electronics mdoules. The system is ideal for small groups of consecutive numbers and covers a large range of ready-printed markers. Being mounted as strips means that they are quickly clipped on in one operation. The printing is easy to read, has excellent contrast, and is available in five widths.

- Large selection of ready-to-use markers
- In strips for fast installation
- Connector markers are suitable for all Weidmüller conductor connectors
- Available as blank cards, MultiCard or as cards with standard printing

### General ordering data

| Order No.  | <u>0473560101</u>                            |  |  |
|------------|--|--|--|
| Туре       | DEK 5 FS 101-150                             |  |  |
| Version    | Terminal markers, Card, 5 x 5 mm, Polyamide, |  |  |
|            | Colour: White                                |  |  |
| GTIN (EAN) | 4008190009632                                |  |  |
| Qty.       | 500 pc(s).                                   |  |  |

# Terminal markers **DEK 5 FS 101-150**

## **Technical data**

**Dimensions** 



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

| Length                                  | 5 mm    | Width                             | 5 mm      |  |
|---|---------|-----------------------------------|-----------|--|
| Net weight                              | 0.04 g  |                                   |           |  |
| Markings                                |         |                                   |           |  |
|   |         |                                   |           |  |
| Cadmium                                 | No      | Colour                            | White     |  |
| Colour of printing                      | black   | Conductor O.D.                    | -         |  |
| Halogen                                 | No      | Material                          | Polyamide |  |
| Material colour according to resistance |         | Operating temperature range, max. |           |  |
| code                                    | 9       |                                   | 100 °C    |  |
| Operating temperature range, min.       | -40 °C  | Orientation of print              | vertical  |  |
| Pin can be written (STI)                | No      | Pitch in mm (P)                   | 5 mm      |  |
| Printed characters                      | Numbers | Printing method                   | MC Laser  |  |
| Silicone                                | No      | UL 94 flammability rating         | V-2       |  |

### Classifications

| ETIM 2.0   | EC000761    | ETIM 3.0   | EC000761    |
|------------|-------------|------------|-------------|
| UNSPSC     | 30-21-18-07 | eClass 4.1 | 24-19-02-19 |
| eClass 5.1 | 27-14-11-37 | eClass 6.0 | 27-14-11-37 |
| eClass 7.0 | 27-14-11-37 |            |             |

#### Approvals

Approvals

