

Printed-circuit board connector - DFK-MSTB 2,5/ 4-G-5,08 WW(1X1) - 0707905

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Header, Nominal current: 12 A, Number of positions: 4, Pitch: 5.08 mm, Connection method: Solder/Slip-on connection, Color: green, Contact surface: Tin

The figure shows the version with solder/spade connections

Why buy this product



Key Commercial Data

Packing unit	1 STK
Minimum order quantity	50 STK
GTIN	 4 017918 004293
GTIN	4017918004293
Weight per Piece (excluding packing)	5.110 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Dimensions

Length	17.5 mm
Pitch	5.08 mm
Dimension a	15.24 mm
Width	40.64 mm
Constructional height	20.2 mm

Printed-circuit board connector - DFK-MSTB 2,5/ 4-G-5,08 WW(1X1) - 0707905

Technical data

Dimensions

Height	29.5 mm
Length of the solder pin	9.3 mm
Pin dimensions	0,8 x 2,8
Hole diameter	3.2 mm

General

Range of articles	DFK-MSTB 2,5/...-G
Rated voltage (III/3)	320 V
Connection in acc. with standard	EN-VDE
Nominal current I _N	12 A
Color	green
Number of positions	4

Standards and Regulations

Connection in acc. with standard	EN-VDE
	CUL

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27141134
eCl@ss 9.0	27141134

ETIM

ETIM 3.0	EC000897
ETIM 4.0	EC001283
ETIM 5.0	EC001283
ETIM 6.0	EC001283

Printed-circuit board connector - DFK-MSTB 2,5/ 4-G-5,08 WW(1X1) - 0707905

Classifications

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121410

Approvals

Approvals

Approvals

cULus Recognized / EAC

Ex Approvals

Approval details

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E60425-19931011
	B		D
Nominal current I _N	15 A		10 A
Nominal voltage U _N	300 V		300 V

EAC		B.01742
-----	--	---------