

07401002 -- Deluxe Cord Grips



Deluxe Cord Grips completely eliminate pull tension on terminals, control cable arc-of-bend, prevent cord pull-out, and provide a liquidtight seal. They are offered with either aluminum, stainless steel or nylon fittings.

Product Specifications

Product Type	Deluxe Cord Grips
Thread Type	N.P.T.
Grip Style and Material	Straight Aluminum Connector Stainless Grip
Grip Cord Range (Diameter)	.312" - .375" (.79 - .95)
Grip Thread Size	3/8"
Deluxe Grip Form Size	F1
Operating Temperature	-30°F to +225°F (-34°C to +107°C)
Mesh Grip Flammability Rating	UL 94-HB
Fitting Flammability Rating	UL 94-V2
Recommended Knockout Hole Size	.671 to .701 (1.70 - 1.78)
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III, Div. 1 & 2.
Dimension A	.88" (2.24) Dia.
Dimension B	.90" (2.29) Ref.
Dimension C	.46" (1.17)
Dimension D	.44" (1.12) Throat Dia.
Dimension E A/C	.99" (2.51)
Dimension E A/F	.88" (2.24)
Dimension F	3/8" - 18
Certifications	UL Listed CSA Certified
UPC Number	78358532182
Weight in LBs	0.25
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

