

Strain Relief

**Flexible Metallic Conduit Grips**

Steel Fitting, Stainless Steel Mesh, Liquidtight, for Liquidtight Flexible Metal Conduit

**Read This Data**

It is important that you read all breaking strength, safety and technical data relating to this product on pages T-103 through T-105.



Straight with Male Fitting



90° Angle with Male Fitting

**Benefits**

- Helps prevent conduit pull-out and damage at the fitting.
- Reduces equipment downtime.

**Straight With Male Fitting**

Conduit Trade Size (Inches)	Trade Size N.P.T. (Inches)	Mesh Length Inches (cm)	Catalog Numbers (Insulated)	Catalog Numbers (Non-insulated)
3/8"	1/2"	3" (7.62)	074093511	074093401
1/2"	1/2"	3 1/2" (8.89)	074093512	074093402
3/4"	3/4"	4" (10.16)	074093513	074093403
1"	1"	5" (12.70)	074093514	074093404
1 1/4"	1 1/4"	6" (15.24)	074093515	074093405
1 1/2"	1 1/2"	6 3/4" (17.14)	074093516	074093406
2"	2"	8" (20.32)	074093518	074093408
2 1/2"	2 1/2"	9 3/4" (24.76)	074093520	074093410
3"	3"	11" (27.94)	074093522	074093412
4"	4"	14" (35.56)	074093526	•

**90° Angle With Male Fitting**

Conduit Trade Size (Inches)	Trade Size N.P.T. (Inches)	Mesh Length Inches (cm)	Catalog Numbers (Insulated)	Catalog Numbers (Non-insulated)
3/8"	1/2"	3" (7.62)	074093541	074093421
1/2"	1/2"	3 1/2" (8.89)	074093542	074093422
3/4"	3/4"	4" (10.16)	074093543	074093423
1"	1"	5" (12.70)	074093544	074093424
1 1/4"	1 1/4"	6" (15.24)	074093545	074093425
1 1/2"	1 1/2"	6 3/4" (17.14)	074093546	074093426
2"	2"	8" (20.32)	074093548	074093428
2 1/2"	2 1/2"	9 3/4" (24.76)	074093550	•
3"	3"	11" (27.94)	074093552	•