

074PG29023 -- Deluxe Cord Grips



Straight Male

Deluxe Cord Grips completely eliminate pull tension on terminals, control cable arc-of-bend, prevent cord pull-out, and provide a liquidtight seal. They are offered with either aluminum, stainless steel or nylon fittings.

Product Specifications

Product Type	Deluxe Cord Grips
Thread Type	P.G.
Grip Style and Material	Straight Aluminum Connector Stainless Grip
Grip Cord Range (Diameter)	.750" - .875" (1.90- 2.22)
Grip Thread Size	PG29
Body Material	Aluminum
Mesh Material	Stainless Steel
Bushing Material	Neoprene
Operating Temperature	-30°F to +225°F (-34°C to +107°C)
Mesh Grip Flammability Rating	UL 94-HB
Fitting Flammability Rating	UL 94-V2
Recommended Knockout Hole Size	29 mm Threaded Hub
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III, Div. 1 & 2.
Certifications	UL Listed CSA Certified
Wet Locations	The products are suitable for use in wet locations so long as a listed nylon fitting is used between box and fitting.
UPC Number	78358532777
Weight in LBs	0.3
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

