

Cable marker - UC-WMTBA (60X11) - 0820468

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Cable marker, Sheet, white, unlabeled, can be labeled with: BLUEMARK CLED, BLUEMARK LED, Plotter, Mounting type: Assembly with cable binders, Cable diameter: >6 mm, Lettering field: 60 x 11 mm



Product Features

- The UC-WMTBA ... UniCard labeling range includes markers that can be secured using standard cable binders
- Thanks to their angular shape the markers fit perfectly onto cables
- For large-surface labeling of conductors and cables > 4 mm in diameter
- Labeling service: Phoenix Contact can custom-label all UniCard markers according to your requirements
- The markers, which are supplied in uniform sheets, can be labeled quickly and easily using the BLUEMARK LED
- The format automatically ensures printing with a high degree of positioning accuracy
- The sheets provide space for including function texts

Key Commercial Data

| Packing unit | 1 pc |
|--------------------------------------|----------|
| Minimum order quantity | 10 pc |
| Weight per Piece (excluding packing) | 10.67 g |
| Custom tariff number | 39269097 |
| Country of origin | Poland |

Technical data

Dimensions

| Width (a) | 60 mm |
|-----------|-------|
| | |

Ambient conditions

| Ambient temperature (operation) | -40 °C 120 °C |
|---------------------------------|---------------|
|---------------------------------|---------------|

General

| Color | white |
|--|--------------------------------|
| Components | free from silicone and halogen |
| Flammability rating according to UL 94 | V2 |
| Material | PA |



Cable marker - UC-WMTBA (60X11) - 0820468

Technical data

General

| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-------------------------------------|-----------------------------|
| Number of individual labels | 4 |
| Number of individual labels per row | 1 |
| Marking mounting type | Assembly with cable binders |

Standards and Regulations

| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|--|-----------------------------|
| Flammability rating according to UL 94 | V2 |

Classifications

eCl@ss

| eCl@ss 4.0 | 24190218 |
|------------|----------|
| eCl@ss 4.1 | 24190218 |
| eCl@ss 5.0 | 27141137 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27400401 |
| eCl@ss 7.0 | 27400401 |
| eCl@ss 8.0 | 27400401 |

ETIM

| ETIM 2.0 | EC000761 |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC001530 |
| ETIM 5.0 | EC001530 |

UNSPSC

| UNSPSC 6.01 | 30211811 |
|---------------|----------|
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com