

## Marker for ENTRELEC terminal blocks - UCT6R-TM 6 - 0830754

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Marker for ENTRELEC terminal blocks, Sheet, white, unlabeled, can be labeled with: THERMOMARK CARD, THERMOMARK CARD 2.0, THERMOMARK PRIME, BLUEMARK ID, BLUEMARK ID COLOR, TOPMARK LASER, TOPMARK NEO, mounting type: snap into tall marker groove, for terminal block width: 6 mm, lettering field size: 4.85 x 9.3 mm, Number of individual labels: 50

### Your advantages

- ✓ UniCard marking for terminal blocks from other manufacturers (ABB) with flat marker groove
- ✓ The multi-section marking strips are easy to fit and can be easily separated if required

### Key Commercial Data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1 pc  |
| Minimum order quantity               | 10 pc   |
| GTIN                                 | <br>4 046356 745604 |
| GTIN                                 | 4046356745604   |
| Weight per Piece (excluding packing) | 12.000 g  |
| Custom tariff number                 | 39269097  |
| Country of origin                    | Poland  |

### Technical data

#### Dimensions

|            |         |
|------------|---------|
| Length (b) | 9.9 mm  |
| Width (a)  | 5.45 mm |
| Height (c) | 2.35 mm |

#### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -40 °C ... 120 °C   |
| Recommended storage conditions  | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |

## Marker for ENTRELEC terminal blocks - UCT6R-TM 6 - 0830754

### Technical data

#### General

|   |  |
|---|--|
| Note  | Can be labeled via thermal transfer      |
| Color   | white                                    |
| Type  | high                                     |
| Components  | free from silicone, halogen, and cadmium |
| Flammability rating according to UL 94                              | V0                                       |
| Material  | PC                                       |
| RoHS compliant  | Yes                                      |
| Wipe resistance   | DIN EN 61010-1 (VDE 0411-1)              |
| Number of individual labels   | 50                                       |
| Number of individual labels per row                                 | 10                                       |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02                     |
| Result  | Test passed                              |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03             |
| Test duration   | 96 h                                     |
| Result of weather resistance test                                   | Test passed                              |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02                |
| Test duration   | 96 h                                     |
| Salt spray testing result   | Test passed                              |
| Wipe resistance of test specification inscriptions                  | DIN EN 61010-1 (VDE 0411-1):2011-07      |
| Result of wipe resistance test                                      | Test passed                              |
| Marking mounting type   | snap into tall marker groove             |
| Result  | Test passed                              |
| Oxygen index (DIN EN ISO 4589-2)                                    | 32.4 %                                   |
| R22   | HL 1 - HL 3                              |
| R23   | HL 1 - HL 3                              |
| R24   | HL 1 - HL 3                              |

#### Standards and Regulations

|  |                             |
|--|-----------------------------|
| Wipe resistance  | DIN EN 61010-1 (VDE 0411-1) |
| Flammability rating according to UL 94                 | V0                          |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3                 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3                 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3                 |

### Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190200 |
|------------|----------|

## Marker for ENTRELEC terminal blocks - UCT6R-TM 6 - 0830754

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.1 | 24190200 |
| eCl@ss 5.0 | 27141100 |
| eCl@ss 5.1 | 27141100 |
| eCl@ss 6.0 | 27141100 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27141137 |
| eCl@ss 9.0 | 27141137 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC000761 |
| ETIM 6.0 | EC000761 |
| ETIM 7.0 | EC000761 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39131505 |
| UNSPSC 18.0   | 39131505 |
| UNSPSC 19.0   | 39131505 |
| UNSPSC 20.0   | 39131505 |
| UNSPSC 21.0   | 39131505 |

### Accessories

#### Accessories

#### Magazine

Magazine - TMP-UCT-MAG24 - 0803368



Magazine, for the THERMOMARK PRIME and the THERMOMARK CARD, for accommodating UCT6R-TM...

