

## **Pushbutton switches**

## 9077.0200

Product number	9077.0200	
Business unit	Switches, Sensors & Controls	
Product family	Pushbutton switches	
Actuation type	direct	
Output	catalogue miniature switch	
Switching function	Changeover switch (DPDT momentary)	
Material fixed contact	CuZn gold-plated	
Contact system	Electrical life	50000
Number of poles	2 - pole	
connections	PCB terminal, sealed with epoxy resin	
Rating IEC	≤ 0.4V A 28 V	
Contact resistance (new condition)	< 50 mOhm	
Insulation resistance (new condition)	> 500 MOhm	
Voltage strength at 250 V	small contact distance	> 500 V
Ambient temperature	-25 °C +70 °C	
Actuators and additional actuators	actuator: PC, natural	
Housing description	cover: PA, black	
	base plate: PA glass fiber-reinforced, gray	
Connection surface	bearing connection	gold plated
	external connection	gold plated
Contact material	CuSn gold-plated	
Contact type	lifting contact	
Operating force	3.5 N	
Total travel / stroke	1.1 mm	
Miscellaneous	corresponding pushbuttons 9090.17 see additional parts	
Type of fastening	pcb assembly	

Technical changes reserved. Dimensions are not binding.

Detailed specifications available on request.