

## Han-Power T 3 x Q2/0 Kunststoff



Image is for illustration purposes only. Please refer to product description.

Part number	09 12 008 4752
Specification	Han-Power T 3 x Q2/0 Kunststoff
HARTING eCatalogue	<a href="https://b2b.harting.com/09120084752">https://b2b.harting.com/09120084752</a>

### Identification

Category	Energy distributors
Series of hoods/housings	Han-Power® T
Element	Energy distributor
Specification	With 3x Han® Q 2/0 In Han® 3 A Housings, bulkhead mounting

### Version

Number of contacts	2
PE contact	Yes

### Technical characteristics

Rated current	40 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3
Rated voltage acc. to UL	600 V
Rated voltage acc. to CSA	600 V
Insulation resistance	$>10^8 \Omega$
Limiting temperature	-40 ... +125 °C
Mating cycles	$\geq 500$
Degree of protection acc. to IEC 60529	IP65 IP67



Pushing Performance

## Material properties

Material (contacts)	Copper alloy
Material (hood/housing)	Polyamide (PA)
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Material (locking)	Polyamide (PA)
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	564b7d75-7bf6-4cfb-acb1-2168eb61b675

## Specifications and approvals

Specifications	EN 60664-1 IEC 61984
UL / CSA	UL 2237 PVVA.E318390 CSA-C22.2 No. 182.3 PVVA7.E318390
CE	Yes

## Commercial data

Packaging size	1
Net weight	80 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27142409 Small distribution board