

Han M23 Cable to cable housing 11-17 mm



Part number	09 15 100 0311
Specification	Han M23 Cable to cable housing 11-17 mm
HARTING eCatalogue	https://b2b.harting.com/09151000311

Identification

Category	Hoods/Housings
Series of hoods/housings Han® M23 Signal	
Type of hood/housing	Panel feed through housing
Description of hood/ housing	Rear mounting

Version

Locking type	Screw locking ComLock rapid locking
Size	M23

Technical characteristics

Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP67 in locked position IP69 / IPX9K acc. to ISO 20653 in locked position
Clamping range	11 17 mm

Material properties

Material (hood/housing)	Copper-zinc alloy
Surface (hood/housing)	Nickel plated
RoHS	compliant with exemption
RoHS exemptions	6c: Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead



Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076

Commercial data

Packaging size	5
Net weight	74 g
Country of origin	Germany
European customs tariff number	85389099