

Han B Base SM LC 1 Lever 1 x Pg16



| • | |
|--------------------|-------------------------------------|
| Part number | 09 30 010 1251 |
| Specification | Han B Base SM LC 1 Lever 1 x Pg16 |
| HARTING eCatalogue | https://b2b.harting.com/09300101251 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Hoods/Housings |
|--------------------------|-------------------------|
| Series of hoods/housings | Han [®] B |
| Type of hood/housing | Surface mounted housing |
| Туре | Low construction |

Version

| Size | 10 B |
|----------------------------|---|
| Version | Side entry |
| Cable entry | 1x Pg 16 |
| Locking type | Single locking lever |
| Han-Easy Lock [®] | Yes |
| Field of application | Standard hoods/housings for industrial connectors |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|-------------|
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 4X |
| | 12 |

Material properties

| Material (hood/housing) | Aluminium die-cast |
|-------------------------|----------------------|
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 7037 (dust grey) |

Page 1 / 2 | Creation date 2022-04-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

| Material (seal) | NBR |
|--|---|
| Material (locking) | Polycarbonate (PC) Stainless steel |
| Colour (locking) | RAL 7037 (dust grey) |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel Naphthalene |
| Specifications and approvals | |

| Approvals | DNV GL |
|--------------------------------|--|
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE | Yes |
| | |
| Commercial data | |
| Packaging size | 1 |
| Net weight | 214 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440202 Shell for industrial connectors |

Page 2 / 2 | Creation date 2022-04-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com