


NOTES:

1. MATERIALS AND FINISHES:
 RP-SMA STR BHD JACK - BRASS, GOLD PLATING


 AMC RA PLUG:
 HOUSING - PBT, BLACK
 CONTACT & GROUND CONTACT - PHOSPHOR BRONZE, GOLD PLATING

 CABLE - 1.13 MM CABLE
2. ELECTRICAL:
 A. IMPEDANCE: 50 OHM
3. PACKAGING:
 A. QUANTITY: SINGLE PACK
 B. MARKING: BAG TO BE MARKED
 "AMPHENOL RF, 95-902-546-XXX AND DATE CODE"

REVISIONS				
REV	DESCRIPTION	DATE	ECN	APPR
A	RELEASE TO MFG.	2/4/2021	--	DG
B	DIMENSION CHANGES	--	--	--
C	UPDATED HEAT SHRINK TUBE LENGTH & CONNECTOR	11-JUN-21	15729	CC



SCALE 1.000



LENGTH TABLE	
PART NUMBER (IMPERIAL)	LENGTH AND TOLERANCE 'L' IN MM (INCHES)
95-902-546-050	50.00 ± 3.81 [1.969 ± 0.150]
95-902-546-100	100.00 ± 3.81 [3.937 ± 0.150]
95-902-546-150	150.00 ± 3.81 [5.906 ± 0.150]
95-902-546-200	200.00 ± 5.08 [7.874 ± 0.200]
95-902-546-250	250.00 ± 5.08 [9.843 ± 0.200]
95-902-546-300	300.00 ± 5.08 [11.811 ± 0.200]

DESIGN REQUIREMENTS:

- | | |
|---|--|
| <input checked="" type="checkbox"/> FREQUENCY: DC - 6 GHz | <input checked="" type="checkbox"/> CONTINUITY |
| <input type="checkbox"/> VSWR: _____ MAX. | <input checked="" type="checkbox"/> HI-POT: 200 VRMS |
| <input type="checkbox"/> INS. LOSS: _____ dB MAX. | <input type="checkbox"/> OTHER: |

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE METRIC (INCHES) AND TOLERANCES ARE:
 <0.5mm = ±0.05mm [$<0.020 = \pm 0.002$]
 >0.5 - 6mm = ±0.1mm [$>0.020 - 0.236 = \pm 0.004$]
 >6.00 - 30mm = ±0.2mm [$>0.236 - 1.181 = \pm 0.008$]
 >30.00 - 120mm = ±0.3mm [$>1.181 - 4.725 = \pm 0.012$]

MATERIAL: SEE NOTES
 ENGR.1: D. GEORGE ENGR.2: DATE: 2/4/2021

TITLE: RP SMA STR BHD JACK FR MT IP67 TO AMC RA PLUG USING 1.13 MM CABLE VARIOUS LENGTH
 SHEET NO. 2 OF 2 SCALE: 5.0:1.0

Amphenol RF

B	DRAWING NO. 95-902-546-XXX	C
	ITEM NO. 95-902-546-XXX	
	PART NO. 95-902-546-XXX	

THIRD ANGLE PROJ. REFERENCE EAR# 10474

ANGLES = ±1°

ENGR.1: D. GEORGE ENGR.2: DATE: 2/4/2021

SHEET NO. 2 OF 2 SCALE: 5.0:1.0

Amphenol RF