


[Home](#) > [Search Tools](#) > [Part Number](#)

Part Number Search

 You Searched For:

Note: Data provided here are offered in good faith and are as reliable and accurate as possible. However, they do not form part of any contract of supply or purchase unless specifically confirmed in writing by an authorized representative of ITT. All information and images shown are the property of ITT ICS and are not to be reproduced in any form without direct authorization from ITT ICS.

ITT ICS strongly recommends that you contact your local ITT Sales Office for confirmation of all the details you obtain through these Web pages. Please be aware that data may change at any time and without notice. For a listing of Sales Offices, local sales support, and authorized distributors please use the "Global Sales Locator" located either to the right of this data or at the top of every page.

Our Descriptive Part Number: MIKQ77PH016

Our Global Manufacturing Part Number: 097194-0004

<input type="checkbox"/>	CONSULT FACTORY	RoHS compliant =	material restrictions of lead, cadmium, hexavalent chromium, mercury, poly bromated biphenyl ether (PBB) and poly bromide diphenyl ether (PBDE) according to directive 2002/95/EC
	CONSULT FACTORY	RoHS compatible =	Compatible with lead free soldering process

Export Compliance		
<input type="checkbox"/>	Country of Compliance	United States
	Export Compliance Notes	Commercial Shipments "C" Controlled by the US Department of Commerce.

Product Datasheet	
Product Sub-Family	MIKQ
Contact Type	Pin
Contact Spacing	.050 (1.27)
Shell Style	Jam nut mount
Contact Arrangement	7
Termination Length Code	6" #26 AWG, MIL-W-16878/4, Type E Teflon, color coded to MIL-STD-681 System I.
Insulator	Glass-reinforced Thermoplastic
Polarization	Keyways
Coupling Nut Material	Brass, Electroless Nickel Plated
Contact Material	50 Microinch, Gold Plated, Copper Alloy
Contact Rating	3 Amps
Coupling	Push / Pull