

## Cable tie - PKB 200X2,5 BK - 1005541

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable tie, resistant to UV rays, dimensions: L x W, 200 x 2.5 mm, color: black

### Product Features

- With the UNIFOX-CT ... cable binder tool, the cable binders can be easily tightened and cut off in one step
- The plastic cable binders are ideal for use with WMTB, KMK 2, and KMK 4 cable markers from Phoenix Contact
- UV stabilized (black), for use in outdoor systems
- For bundling control lines and cables
- The cable binders can be used indoors and outdoors even under unfavorable industrial conditions
- Transparent, for standard applications

### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	1000 pc
Weight per Piece (excluding packing)	0.6 g
Custom tariff number	39269097
Country of origin	United States

### Technical data

#### Dimensions

Length (b)	200 mm
Width (a)	2.5 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

#### General

Color	black
Components	Halogen-free
Flammability rating according to UL 94	V2
Material	PA

## Cable tie - PKB 200X2,5 BK - 1005541

### Technical data

#### Standards and Regulations

Resistance to UV radiation	yes
Flammability rating according to UL 94	V2

### Classifications

#### eCl@ss

eCl@ss 4.0	27140702
eCl@ss 4.1	27140702
eCl@ss 5.0	27140702
eCl@ss 5.1	27140702
eCl@ss 6.0	27140702
eCl@ss 7.0	27140702
eCl@ss 8.0	27140702

#### ETIM

ETIM 2.0	EC000046
ETIM 3.0	EC000046
ETIM 4.0	EC000046
ETIM 5.0	EC000046

#### UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703