

**Cable glands  
VG PG21-MS54 ZR 10-19**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Each size of this standard cable gland consists of multiple, separable seal inserts (onion-ring shaped). By separating these individual inserts, it becomes possible to install cables of varying diameters (from 4 mm to 41 mm) into the cable gland.

**General ordering data**

Type	VG PG21-MS54 ZR 10-19
Order No.	<a href="#">1009630000</a>
Version	cable glands, Brass, nickel-plated, External thread: PG 21
GTIN (EAN)	4032248714407
Qty.	25 pc(s).

**Datenblatt**

**Cable glands  
VG PG21-MS54 ZR 10-19**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technische Daten**

**Dimensions and weights**

Length	29.5 mm	Net weight	65 g
--------	---------	------------	------

**General information**

AF size 1	28 mm	AF size 2	30 mm
Cable gland	PG	Clamping range, max.	19 mm
Clamping range, min.	10 mm	External thread	PG 21
Length of thread	7 mm	Material	Brass, nickel-plated
Notch multi-layer sealing diameter 1	10 mm	Notch multi-layer sealing diameter 2	13 mm
Notch multi-layer sealing diameter 3	16 mm	Notch multi-layer sealing diameter 4	19 mm
Operating temperature range, max.	80 °C	Operating temperature range, min.	-20 °C
Seal insert	NBR	Torque for cap nut, max.	6.7 Nm
Torque for cap nut, min.	6.7 Nm	Torque for connecting adapter, max.	10 Nm
Torque for connecting adapter, min.	10 Nm		


**Classifications**

eClass 6.2	27-18-92-34	eClass 7.1	27-18-92-34
------------	-------------	------------	-------------

**Product information**

Descriptive text ordering data	D1-D4 are the removable seal incisions from 4 mm to 41 mm.
--------------------------------	--

**Approvals**

Approvals	
ROHS	Conform