

TECHNICIAN AIDS

White Glazed EGG INSULATOR

A very high-strength insulator made from best quality steatite ceramic. Designed with fully curved surfaces to prevent cutting and chafing of wires.



No. J852

INSULATOR

These insulators are lightweight, durable molded tenite plastic. Dielectric strength is comparable to its ceramic predecessor without susceptibility to cracking or breakage under impact or severe temperature change, Weatherproof.

No. 2130CP



Economy SOLDER WICK

Supplied on 5 ft. spool in .08" (2.0mm) width. Extremely high absorption capacity.

No. HSW15



ULTRA-CHEM Heatsink Compound

This heatsink compound contains silicone and is used to transfer heat away from transistors and IC's for them to run cooler.

No. 50-819 2oz Tube

No. 50-820 3g Tube



ULTRA-CHEM Heatsink Compound Type II

Silicon FREE heat sink compound which will not migrate and meets MIL-C-47113 properties. It is used in applications where contamination is a problem such as wave soldering, and operates at a wider temperature range (-40°-392°F)

No. 50-850 4oz Tube



ULTRA-CHEM Swabs

No. 50-150

Double Tipped 6" (100 pk)



No. 50-288

Chamois 3/8" X 4 1/2" (25 pk)



I.C. EXTRACTION TOOL



Economical spring steel tool, one-piece construction, insulated, will work on all I.C. devices from 8 pin to 24 pin.

No. 10230

PLASTIC RESTORER REFINISHING KIT

These products will work on Plexiglass®, Lexan®, Lucite®, UVEX® and Acrylite®. Polish #1 will clear up most surface blemishes on meter faces, etc. Polish #2 is for the truly bad situations; it actually removes damage instead of filling it. These polishes are free of any offensive odors and there is no toxic risk. The kit comes complete with handy polishing cloth. It's great for instrument faces, plexiglass windows, convertible rear windows, computer screens, copiers, safety goggles and motorcycle windows.



No. 10300 - Kit

No. 10301 - Polish #1

No. 10302 - Polish #2

HEAT GUN

The Philmore No. HD866 is a dual range gun. The low range covers 500° F and the high range covers 900° F - 1100° F. This fine quality product can be used for:

- Heat shrink tubing
- Paint removal
- Drying metal
- Drying ignition systems
- Bending plastic/plexiglass
- Window shrink films
- Frozen locks

UL LISTED
117VAC
1100 Watts
Includes (2)
tips and tip
removal tool.

No. HD866



VACUUM SOLDER REMOVAL TOOL



Makes removal of molten solder from p.c. board easy. One hand operation. Nose is removable for easy clean-out. All-metal construction provides long, trouble-free service.

No. 10320

No. 10325 - Replacement Anti-Static Tip and "O" Ring

PLCC EXTRACTION TOOL

A tool for removing square I.C.'s such as CPU's, from their sockets without damage. Grips PLCC's by opposite corners; makes removal fast and very easy. Safe for the I.C.



No. 10270