

**W-Series  
WQV 10/2**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

|            |   |
|------------|---|
| Type       | WQV 10/2  |
| Order No.  | <a href="#">1052560000</a>  |
| Version    | W-Series, Cross-connector, For the terminals,<br>Number of poles: 2 |
| GTIN (EAN) | 4008 190154943  |
| Qty.       | 50 pc(s).   |

Creation date August 22, 2020 9:07:20 AM CEST

Catalogue status 14.08.2020 / We reserve the right to make technical changes.

**W-Series  
WQV 10/2**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 7.55 mm | Width (inches)  | 0.297 inch |
| Height     | 16.9 mm | Height (inches) | 0.665 inch |
| Depth      | 18 mm   | Depth (inches)  | 0.709 inch |
| Net weight | 3.6 g   |                 |            |

**Temperatures**

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature, max.        | 55 °C          | Storage temperature, min.        | -25 °C |
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C         |                                  |        |

**Material data**

|                           |       |        |        |
|---------------------------|-------|--------|--------|
| Material                  | PA 66 | Colour | yellow |
| UL 94 flammability rating | V-0   |        |        |

**System specifications**

|         |                   |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

**Additional technical data**

|                     |                 |                |                 |
|---------------------|-----------------|----------------|-----------------|
| Installation advice | Direct mounting | Type of fixing | when screwed in |
|---------------------|-----------------|----------------|-----------------|

**Cross-connector**

|                                     |                 |  |              |
|-------------------------------------|-----------------|--|--------------|
| Number of cross-connected terminals | 2               | Rated current, 2-pole                    | 57 A         |
| Rated current, multi-pole           | 57 A            | Tightening torque range for fixing screw | 0.5...1.0 Nm |
| Type                                | Cross-connector |  |              |

**Dimensions**

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 9.9 mm |
|-----------------|--------|

**Rating data**

|               |      |
|---------------|------|
| Rated current | 76 A |
|---------------|------|

**Classifications**

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0   | EC000489    |
| eClass 9.0  | 27-14-11-40 | eClass 9.1 | 27-14-11-40 |
| eClass 10.0 | 27-14-11-40 | UNSPSC     | 30-21-18-01 |

**Approvals**

|           |   |
|-----------|---|
| Approvals |  |
| ROHS      | Conform   |

**W-Series  
WQV 10/2**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data****Downloads**

---

|   |  |
|---|--|
| Approval/Certificate/Document of Conformity | <a href="#">EAC certificate</a>  |
| Brochure/Catalogue                          | <a href="#">CAT 1 TERM 16/17 EN</a>  |
| Engineering Data                            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>   |
| Engineering Data                            | <a href="#">08873_WQV_10-2_DXF.dxf</a><br><a href="#">STEP</a>                           |
| User Documentation                          | <a href="#">Beipackzettel_WQV.pdf</a><br><a href="#">StorageConditionsTerminalBlocks</a> |

---