


## **RF CONNECTORS**



✓ Active

TE CONNECTIVITY (TE) 2058 5269 00

Subminiature Coax | SM , SMA

1053251-1

TE Internal Number: 1053251-1

Not EU RoHS Compliant Not EU ELV Compliant

**Connector Interface SMA** 

**Connector Style** Jack

Mated Outer Diameter (Approximate) 6.35 mm [.25 in]

Impedance ( $\Omega$ ) 50

**Operating Frequency (GHz)** 18



**PRODUCT DRAWING** 

English



**★** 3D PDF

## **DOCUMENTATION**

**Product Drawings** 

## OSM ENVIRONMENTALLY DURABLE JACK RECEPTACLE WITH SLIDING CONTACT, HERMETICALLY SEALED

PDF (TIFF AVAILABLE)

**English** 

**CAD Files** 

**3D PDF** 

PDF

3D

## **Customer View Model**

2D\_DXF.ZIP

**English** 

3D_IGS.ZIP
English Control of the Control of th
Customer View Model
3D_STP.ZIP
English
Instruction Sheets
Instruction Sheet (U.S.)
OSM Panel Feedthrough Hermetic Jack Receptacle With Metal Gasket And Sliding Contact 1091898-1, 1053251-1, 1254098-1, And 1053252-1
TIF
English
OSM Panel Feedthrough Hermetic Jack Receptacle With Metal Gasket And Sliding Contact 1091898-1, 1053251-1, 1254098-1, And 1053252-1
PDF  English
Liigiisii
FEATURES +
Please review product documents or contact us for the latest agency approval information.
Please Note: Use the Product Drawing for all design activity.
Product Type Features
Connector Interface SMA
Connector Style Jack
Electrical Characteristics
Impedance ( $\Omega$ ) 50
Body Features
Cable Connector Orientation Straight
Body Material Stainless Steel
Body Plating Material Gold
Contact Features
Center Contact Plating Material Gold over Copper
Center Contact Material Beryllium Copper
Connector Product Type Connector Assembly  RF Connector Contact Configuration Captivated Contacts
Mechanical Attachment
Panel Attachment Style Front Mount, Rear Mount
Dimensions

**Customer View Model** 

Mated Outer Diameter (Approximate) 6.35 mm [.25 in]  Length 11.5 mm [.453 in]	
Operation/Application	
Operating Frequency (GHz) 18	
Packaging Features	
Packaging Method Carton	
Other	
Dielectric Material TFE Fluorocarbon	
Gasket Material Steel	
Comment Hermetically Sealed	
PRODUCT COMPLIANCE	+
Statement of Compliance	
Statement of Compliance	
PDF	