

RJ45 socket insert - CUC-SP-J1ST-A/R4LT-LED - 1149867


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RJ45 socket insert, degree of protection: IP20, 10 Gbps, connection method: Solder connection



Key Commercial Data

Packing unit	80 pc
Minimum order quantity	80 pc
GTIN	 4 063151 145866
GTIN	4063151145866
Weight per Piece (excluding packing)	22.220 g
Custom tariff number	85366930
Note	Made to Order (non-returnable)

Technical data

Mechanical characteristics

Connection method	Solder connection
Number of slots	1
Rated voltage (III/2)	72 V DC
Rated surge voltage (III/3)	1.5 kV
Overvoltage category	I
Insertion/withdrawal cycles	750
Number of positions	8
Degree of protection	IP20
Degree of pollution	2
Weight	22.22 g

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

RJ45 socket insert - CUC-SP-J1ST-A/R4LT-LED - 1149867

Technical data

Material data

Contact surface material	AU
Contact material	Phosphor bronze
Contact carrier material	PA9T GF
Width	16.18 mm
Height	11.3 mm
Length	15 mm

Electrical characteristics

GRP transmission properties	Data transmission 10 Gbps
Transmission speed	10 Gbps
Rated current	1.5 A
Overvoltage category	I
Degree of pollution	2
Insulation resistance	> 500 MΩ
Test voltage Core/Core	1 kV DC
Test voltage Core/Shield	1.5 kV DC

Standards and Regulations

Flame resistance	UL 94 V0
Halogen-free	no
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 9.0	27440205
------------	----------

ETIM

ETIM 5.0	EC000438
----------	----------