

**SAI-M23-KSC-0,25-1.0**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Drawing**

The M23 round plug-in connectors offer a high number of mating cycles, high current-carrying capacity and high contact-density coupled with minimum dimensions. Enclosures, inserts and crimp contacts need to be ordered separately.

**General ordering data**

Type	SAI-M23-KSC-0,25-1.0
Order No.	<a href="#">1170390000</a>
Version	Sensor/Actuator plug-in connector, Crimp contact
GTIN (EAN)	4032248962105
Qty.	50 pc(s).

**SAI-M23-KSC-0,25-1.0**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Net weight 0.36 g

**Temperatures**

Operating temperature, max. 125 °C      Operating temperature, min. -40 °C

**Environmental Product Compliance**

REACH SVHC Lead 7439-92-1

**Standards**

Certificate No. (UR) E344862

**General data**

Conductor O.D.	-	Conductor cross-section, max.	0.25 mm <sup>2</sup>
Conductor cross-section, min.	1 mm <sup>2</sup>	Contact material	Copper-Zinc alloy
Contact surface	Gold-plated	Insulation strength	> 10 <sup>10</sup> Ω
Plugging cycles	> 1000	Type of connection	Crimp connection

**Classifications**

ETIM 6.0	EC000796	ETIM 7.0	EC000796
eClass 9.0	27-44-02-92	eClass 9.1	27-44-02-90
eClass 10.0	27-44-02-92		

**Product information**

Product information Enclosures, inserts and crimp contacts need to be ordered separately.

**Approvals**

Approvals



ROHS Conform

**Downloads**

Brochure/Catalogue	<a href="#">CAT 8 SAI 15/16 EN</a> <a href="#">FL FIELDWIRING EN</a>
Engineering Data	<a href="#">STEP</a>