

HDMI High Speed Cable with Ethernet Type A Male to Type A Male, White



**RoHS
Compliant**

Specifications:

Material

HDMI Cable : [(7/0.10BC × 1P + 7/0.10BC + AM) × 5 Pcs + (7/0.10BC) × 4C + AM + 7/0.12CCS + 128/0.12ALM + White PVC Jacket
OD : Ø6 ±0.2mm

High Speed HDMI cable with Ethernet

HDMI Type A Male : Black Insulation, Gold plated contacts, Nickel plated shell

All Hood : Molded White PVC


Electrical

100% open and short test

Conductor Resistance : 5Ω Max.


Insulation Resistance : 10MΩ Min.

HDTV-DVD test : 1,080p



Dimensions : Millimetres

Pin Out



Part Number Table

Description	Length (L)	Part Number
HDMI High Speed Cable with Ethernet; Type A Male to Type A Male, White	1,000 ±30mm	11.99.5701
	2,000 ±50mm	11.99.5702
	3,000 ±70mm	11.99.5703
	5,000 ±70mm	11.99.5705

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

