

Crimping pliers - CRIMPFOX-RC 2,5 - 1212063

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Crimping pliers, for uninsulated cable lugs, 0.34 - 2.5 mm², indent crimp

Product Features

- Compact and lightweight design
- Ergonomically designed handles ensure an optimum grip and help avoid fatigue when working
- Crimping pliers for uninsulated cable lugs
- Compact and lightweight design
- Marked die stations for precise processing of corresponding cross sections
- Unlockable pressure lock
- Lateral conductor entry
- Consistently high crimping quality



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	440.0 g
Custom tariff number	82032000
Country of origin	Sweden

Technical data

Dimensions

Length (b)	198 mm
Width (a)	18 mm
Height	59 mm

General

Color	black
-------	-------

Crimping pliers - CRIMPFOX-RC 2,5 - 1212063

Technical data

General

Compression	Indent crimp
Type of contact	Non-insulated cable lugs
Designation	Crimping position 1
Min. cross section	0.34 mm ²
Max. cross section	0.75 mm ²
AWG min	22
AWG max	20
Designation	Crimping position 2
Min. cross section	0.75 mm ²
Max. cross section	1.5 mm ²
AWG min	14
AWG max	16
Designation	Crimping position 3
Min. cross section	1.5 mm ²
Max. cross section	2.5 mm ²
AWG min	16
AWG max	14

Classifications

eCl@ss

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	21043811
eCl@ss 7.0	21043811
eCl@ss 8.0	21049090

ETIM

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186
ETIM 5.0	EC000168

UNSPSC

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518

Crimping pliers - CRIMPFOX-RC 2,5 - 1212063

Classifications

UNSPSC

UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Drawings

Product drawing

