1-2199230-5 V ACTIVE

M.2 NGFF

TE Internal #: 1-2199230-5

M.2 NGFF, M.2 Connectors, Connector Height .165 in [4.2 mm], M

Keying Code, Gold, Board-to-Board, 67 Position, .5mm [.02in]

Centerline

View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > M.2 Connectors > M.2 CONNECTORS











Connector Height: 4.2 mm [.165 in]

Keying Code: M

Contact Mating Area Plating Material: Gold

Connector System: Board-to-Board

Number of Positions: 67

All M.2 CONNECTORS (29)

Features

Product Type Features

Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Rows	2
PCB Mount Orientation	Right Angle
Keying Code	M
Number of Positions	67

Electrical Characteristics

Contact Features

15 μin



PCB Contact Termination Area Plating Material Finish	Matte
PCB Contact Termination Area Plating Material	Gold Flash, Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold
Contact Current Rating (Max)	.5 A
Termination Features	
Termination Method to Printed Circuit Board	Surface Mount
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	High Temperature Thermoplastic
Housing Color	Black
Centerline (Pitch)	.5 mm[.02 in]
Dimensions	
Connector Length	21.9 mm[.862 in]
Connector Width	8.7 mm[.343 in]
Connector Height	4.2 mm[.165 in]
Usage Conditions	
Operating Temperature Range	-40 - 80 °C[-40 - 176 °F]
Operation/Application	
Circuit Application	Power
Packaging Features	
	T 0.D 1

Product Compliance

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUL 2021 (219) Candidate List Declared Against: JUL 2021 (219)

Tape & Reel



Does no	t contain	RFACH	SVHC
D062 110	t Contain	NL A C H	\mathcal{I}

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Reflow solder capable to 245°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series M.2 NGFF



Customers Also Bought





TE Part #1-2199119-5 M.2 0.5PITCH 3.2H KEY M 15U" AU



TE Part #5535034-5
ASSY,RECEPTACLE,EUROCARD,TYPE
C/2,L-FREE



TE Part #120955-1
TE UPM R/A Header 5P HC Power,
LLLLL



TE Part #120953-4
UPM EXPANDED RCPT ASSEMBLY



TE Part #1551920-2 zQSFP+ connector assembly



TE Part #120957-2 UPM EXPANDED PIN ASSEMBLY



TE Part #1-2340321-2 ASSY STRADDLE MOUNT 168P 076 SLIVER 2.0



TE Part #1-2328461-1 280 POS., CONNECTOR ASSEMBLY, SLIVER 2.0



TE Part #1410278-2 MULTIGIG RT PWR .8" VRT RCP 2P PBFR



Documents

Product Drawings

M.2 0.5PITCH 4.2H KEY M 15U" AU

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2199230-5_B2.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2199230-5_B2.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2199230-5_B2.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

M.2 NGFF, M.2 Connectors, Connector Height .165 in [4.2 mm], M Keying Code, Gold, Board-to-Board, 67 Position, .5mm [.02in] Centerline



1-1773702-1_NGFF_QRG-EN

English

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_1-2199230-5_07072016357_dmtec

English

MD_1-2199230-5_07072016357_dmtec

English