1255AY-1R2N# "#" indicates a package specification code.













< List of part numbers with package codes > 1255AY-1R2N=P3

Shape





Rated current (Isat) is specified when the decrease of the initial inductance value at 30%. (The ambient reference temperature is 20°C.) Rated current (Itemp) is specified when temperature of inductor the is raised 40°C by DC current. (The ambient reference temperature is 20°C.)

References

Packaging code	Specifications	Minimum quantity
=P3	φ330mm Embossed taping	1500

	Mass (Typ.)	
1 piece		0.562g

Specifications

Inductance	1.2μH ±30%
Inductance test frequency	0.1MHz
Rated current (Isat) (Based on Inductance change)	8400mA
Rated current (Itemp) (Based on Temperature rise)	5900mA
Max. of DC resistance	0.0144Ω
Avg. of DC resistance	0.012Ω±20%
Operating temperature range (Self-temperature rise is included)	-40~85℃
Class of magnetic shield	Magnetic Resin
Series	DG6045C

1 of 2



^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




^{2.} This datasheet has only typical specifications because there is no space for detailed specifications

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)

Inductance-Current characteristics (Typ.)



Temperature rise characteristics (Typ.)



2 of 2



1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

