L

NTUS KEY INDUSTRIES SE	VITCH [™] Toggle Switches » TW) 2 pole, 3 position, Solder terminal, rt Number MS27754-34L Sales & Service ② Distributor Inventory ②	SALES & SUPPORT Contacts Customer Service Technical Support Global Sales & Service View Site Demo Site Comments? meet dr. larry VIDEO - Dr. Larry Goldstein explains our newest and best technologies. Meet Dr. Larry Wide Dr. Larry Cogin to iCOM Login to Rep/AD Portal Login to Digital University
VI-12L ne : Products : Switches » MICRO SW TW Series Toggle Switch, Locking Lever, Military Par Vi- e e tual duct pearance y vary.	2 pole, 3 position, Solder terminal, rtr Number MS27754-34L Sales & Service Distributor Inventory an Application Notes Opposite	Customer Service Technical Support Global Sales & Service View Site Demo Site Comments? Met Dr. Larry Meet Dr. Larry Meet Dr. Larry Meet Dr. Larry Meet Dr. Larry Met Dr. Larry Met Dr. Larry Met Dr. Larry
ne : Products : Switches » MICRO SW TW Series Toggle Switch, Locking Lever, Military Pa Understand but bacarance y vary.	2 pole, 3 position, Solder terminal, rtr Number MS27754-34L Sales & Service Distributor Inventory an Application Notes Opposite	Customer Service Technical Support Global Sales & Service View Site Demo Site Comments? Met Dr. Larry Meet Dr. Larry Meet Dr. Larry Meet Dr. Larry Meet Dr. Larry Met Dr. Larry Met Dr. Larry Met Dr. Larry
Locking Lever, Military Pa	n Application Notes	Technical Support Global Sales & Service View Site Demo Site Comments? MDEO - Dr. Larry MOEO - Dr. Larry WDEO - Dr. Larry Woet Dr. Larry Met Dr. Lary Met Dr. Larry Met Dr. Lary M
val uduct pearance y vary. overview Specs Documentation roduct Specifications	n Application Notes Opposite	VIDEO - Dr. Larry Goldstein explains our newest and best technologies. Meet Dr. Larry Meet Dr. Larry my link Login to iCOM Login to iCOM Login to Rep/AD Portal Login to Digital University
oduct Specifications	n Application Notes Opposite	Login to iCOM Login to Rep/AD Portal Login to Digital University
oduct Specifications	Opposite	Login to Rep/AD Portal Login to Digital University
	Maintained Maintained Position Position 3 2 1 3 2 1 3 2 1	HONEYWELL ANNOUNCES ADDITION TO RELIALIGN™ RESIDENTIAL DOOR INTERLOCK SWITCHES THAT FEATURE RUGGED, PLASTIC HOUSING
oduct Type ver Lock	6 5 4 6 5 4 6 5 4 ON ON ON MICRO SWITCH [™] Toggle Switch	HONEYWELL RELEASES UNLIMITE POTENTIAL WITH NEW LIMITLESS™ WIRELESS SWITCHES HONEYWELL'S XYR6000 WIRELESS POSITION SENSOR ENABLES MONITORING IN HAZARDOUS AREAS AND REMOTE LOCATIONS
	Locked out of extreme position (Keyway side)	MICRO SWITCH Anniversary site
npere/Voltage Range (Resistive Load) rcuitry tion punting mriination L Spec. Number	0.1 A to 5.0 A at 0.5 Vac to 115 Vac,0.1 A to 5.0 A at 0.5 Vdc to 28 Vdc DPDT 3 position Bushing 15/32 in Solder MS27754-34L	
ver Type J/CSA omment railability JSPSC Code	Locking L117: 5 A at 125 Vac Fine silver contacts Global 30211908	
	ver Lock hpere/Voltage Range (Resistive Load) rouitry uoting rmination L Spec. Number ver Type JCSA imment ailability ISPSC Code	ON ON ON obduct Type MICRO SWITCH™ Toggle Switch ver Lock Image: Cooked out of extreme position (Keyvay side) npere/Voltage Range (Resistive Load) 0.1 A to 5.0 A at 0.5 Vac to 115 Vac,0.1 A to 5.0 A at 0.5 Vdc to 28 Vdc rouitry DPDT tion 3 position punting Bushing 15/32 in rmination Solder L Spec. Number MS27754:34L ver Type Locking /CSA L117: 5 A at 125 Vac mment Fine silver contacts ailability Global

Terms & Conditions | Privacy Statement | Site Map