PRODUCTS ▼

H ABOUTUS ▼

12TW1-1M

Products > Switches > Toggle Switches > TW Series > 12TW1-1M

Overview

MICRO SWITCH TW Series Toggle Switch, 2 pole, 3 position, Solder terminal, Locking Lever, Military Part Number MS27721-21-1M....

View More



MICRO SWITCH

Toggle

















Technical Specifications

Series Name	TW
Ampere/Voltage Range (Resistive Load)	0.1 A to 5.0 A at 0.5 Vac to 115 Vac 0.1 A to 5.0 A at 0.5 Vdc to 28 Vdc
Action	3 position
Mounting	Bushing 15/32 in
MIL Spec. Number	MS27721- 21-1M

		Switch		
	Circuitry	DPDT		
	Circuitry/Operating action	Reyway Position Posit		
	Termination	Solder		
	Lever Type	Locking		

View documents in: English

English

7MB

Product Type

View More

Documents

TITLE	TYPE	LANGUAGE	SIZE
12TW1-1M highres photo	Photo	English	3МВ
MICRO SWITCH TW Series Miniature Military-Grade Toggle Switches	Datasheet	English	1MB
12TW1-1M lowres photo	Photo	English	253KB
Sensors and Switches in Oil	Application	English	7MD

Note

View More

Product Features

- Qualified to MIL-DTL-83731
- Save space and weight

Rig Applications

- SPDT and DPDT circuitry
- Temperature range: -65 °C to 71 °C [-85 °F to 160 °F]
- Sealed bushing versions
- Choice of 1/4 in or 15/32 in bushing
- Color tab available on 15/32 in. bushing
- UL recognized

Applications

- Industrial machinery and equipment
- Military and commercial aviation
- Construction equipment
- Test instruments
- Agricultural machinery
- Process control
- Medical instrumentation

NAVIGATION LINKS

HOME PAGE

PRODUCTS

DISTRIBUTOR INVENTORY

INDUSTRIES SUPPORT

NEWS & EVENTS

.....

ABOUT US

DISTRIBUTOR LINKS

ECOM LOGIN

LEARN CENTER

REQUEST ACCESS TO ECOM

SALES/AD PORTAL LOGIN

SALES/AD PORTAL ACCESS REQUEST

SAMPLE REQUEST

SUPPLIER MICROSITE

LANGUAGE



SOCIAL MEDIA



SITE INFORMATION

PRIVACY STATEMENT

SITEMAP

TERMS & CONDITIONS

COPYRIGHT © 2018 HONEYWELL INTERNATIONAL INC.