

## RAFIX 22 FS $^{\scriptscriptstyle +}$ - Mushroom-headed pushbutton, momentary, non-illuminated

## 1.30.276.701/0000



General information	
Form of lens	conical mushroom form
Color of lens	black
Form of collar	round
Dimensions	
Mushroom Diameter	30 mm
Overall height	33.2 mm
Mounting depth	PCB 9.2 mm, QC 27 mm
Mounting hole	22.3 mm
Diameter of collar	29.8 mm
Mechanical design	
Mounting	ring nut
Contact function	momentary
Illuminability	no
Reset	-
Torque for nut ring	1.2 Nm
Mechanical characteristics	
Robustness max.	100 N
Nobustiness max.	100 N
Other specifications	
Ambient temp. operating min.	-25 °C
Ambient temp. operating max.	+70 °C
Storage temperature min.	40 °C
Storage temperature max.	+80 °C
Operating life	50,000 cycle
B10	65,000 cycle
Degree of protection from front side	IP65 (DIN EN 60529)
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Salt spray	IEC 600 68-2-11
Robustness	acc. to IEC 600 68-2-3 und 2-30
ROHS compliant	yes
REACH compliant	yes



## Panel cut-out to IEC 60947-5-1



