

**SAK Series**  
**Q 2 DLI****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com**Product image****Signal wiring**

Tailored and particularly compact: with our AIO initiator/actuator terminal blocks, you are relying on an application-optimised solution for signal wiring. We also offer you other terminal blocks featuring spring and screw connection technology for signal wiring.

**General ordering data**

|            |                                                                            |
|------------|----------------------------------------------------------------------------|
| Type       | Q 2 DLI                                                                    |
| Order No.  | <a href="#">1312500000</a>                                                 |
| Version    | SAK Series, Cross-connector, for cross-connection link, Number of poles: 2 |
| GTIN (EAN) | 4008 190039837                                                             |
| Qty.       | 50 pc(s).                                                                  |

Creation date August 22, 2020 9:14:09 AM CEST

Catalogue status 14.08.2020 / We reserve the right to make technical changes.

## Data sheet

### SAK Series Q 2 DLI

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 11.1 mm | Width (inches)  | 0.437 inch |
| Height     | 4 mm    | Height (inches) | 0.157 inch |
| Depth      | 8 mm    | Depth (inches)  | 0.315 inch |
| Net weight | 1.4 g   |                 |            |

### Temperatures

|                           |                |                           |        |
|---------------------------|----------------|---------------------------|--------|
| Storage temperature, max. | 55 °C          | Storage temperature, min. | -25 °C |
| Storage temperature       | -25 °C...55 °C |                           |        |

### Material data

|          |      |        |      |
|----------|------|--------|------|
| Material | CuSn | Colour | grey |
|----------|------|--------|------|

### System specifications

|         |                           |
|---------|---------------------------|
| Version | for cross-connection link |
|---------|---------------------------|

### Additional technical data

|                          |                 |                     |                 |
|--------------------------|-----------------|---------------------|-----------------|
| Explosion-tested version | No              | Installation advice | Direct mounting |
| Type of fixing           | when screwed in |                     |                 |

### Dimensions

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 6.1 mm |
|-----------------|--------|

### Rating data

|               |      |
|---------------|------|
| Rated current | 24 A |
|---------------|------|

### Classifications

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0   | EC000489    |
| eClass 9.0  | 27-14-11-40 | eClass 9.1 | 27-14-11-40 |
| eClass 10.0 | 27-14-11-40 | UNSPSC     | 30-21-18-01 |

### Approvals

Approvals



ROHS Conform

### Downloads

|                                             |                                                 |
|---------------------------------------------|-------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">EAC certificate</a>                 |
| Brochure/Catalogue                          | <a href="#">CAT 1 TERM 16/17 EN</a>             |
| Engineering Data                            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>        |
| Engineering Data                            | <a href="#">STEP</a>                            |
| User Documentation                          | <a href="#">StorageConditionsTerminalBlocks</a> |

Creation date August 22, 2020 9:14:09 AM CEST

Catalogue status 14.08.2020 / We reserve the right to make technical changes.