

www.tycoident.com

Issue: 2 Date: July 2006

Document number: TTDS-009



TECHNICAL DATA SHEET 1330-0607 Thermal Transfer Ribbons

MATERIAL DESCRIPTION:	This high durable black resin thermal transfer ribbon is suitable for use on Polyesters and general pressure sensitive labels. When printed on Tyco Recommended labels and printers it gives exceptional abrasion and solvent Resistance.
APPLICABLE PRINTERS	T208M, T212M: T308S, T312S, T312M T408M:
PRODUCTS:	T300 = HPK, HPKTM, HLTM, TP tape, TTP, SP, WP, MP, CP, HW, HM, MV, TN, WV T408M = HPK, HPKTM, HLTM, TTP, SP, WP, MP, CP, HW, HM, MV, TN, WV T200 = HPK, TTP, SP, NC, WP, MP, CP, HW, HM, MV, TN, WV
SHELF LIFE:	2 years when stored between -5°c (23F) and 40°c (104F)
COLOR:	Black.
DIMENSIONS:	300m x 110mm (984' x 4.33") for 1330-0607-10 74m x 110mm (242' x 4.33") for 1330-0607-T200
WINDING DIRECTION:	Ink side out
ORDERING INFORMATION:	1330-0607-10 for all T300, T400, series printers 1330-0607-T200 for all T200 series printers
PRINT PERFORMANCE	See Individual product technical data sheets

Page 1 of 1

CLIDE		
Business locations:		
N America: + 1 650 361 3860 (West Coast)	N America: + 1 401 751 6505 (East Coast)	
Germany: + 49 (0) 6074 89080	France: + 33 (0) 476 099696	
UK: + 44 (0) 1495 244000 (Labels)	UK: + 44 (0) 1793 528171 (Other products)	
Japan: + 81 (0) 44 900 5102	Singapore: + 65 (0) 4866 151	
	TILS I ATECT	
	s, however, should independently evaluate the suitability of each product for their	
	ess of the information and disclaims any liability regarding its use. Tyco Electronics	
	product and in no case will Tyco Electronics be liable for any incidental, indirect or	
	yco Electronics Specifications are subject to change without notice. In addition Tyco	
Electronics reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable		
specification.		