
Overall Width (OW) Opening **STATSHIELD® Static Shielding Bag Metal In Construction** Discharge Shielding RoHS Length (L) ATTENTION: ATTENTION: Contents may be Static Sensitive OTHER PET/ALU/PE Handling Precautions Required DescoIndustries.com Made in America Date & Lot Code Printed for QC Traceablility Weld Weld Width (W Seal



Side Weld Seals 3/8 in. (±0.10)

Mixed Unsortable Plastic Scrap

Mixed unsortable plastic scrap shall contain assorted plastics of multiple grades that are co-extruded, bonded or laminated together which are unsortable into individual grades

Desco's bags are recyclable

Soft Fold Bottom

Statshield® bags are packaged 100 per package in an oversized shielding bag. See Shielding Bag Storage at <u>TB-7057</u>.

STATSHIELD® METAL-IN SERIES

Specifications:

Standard Document

ANSI/ESD S541 (ANSI/ESD S20.20)

ANSI/ESD S11.4

Electrical PropertiesSurface Resistance: Typical Values

Outer Surface 1×10^4 to $< 1 \times 10^{11}$ ohms Inner Surface 1×10^4 to $< 1 \times 10^{11}$ ohms Discharge Shielding < 20 nJ

Charge Generation Teflon: 0.09 nC/sq. in.

Quartz: 0.01 nC/sq. in.

Capacitance Probe (to dissipate 1 KV) <30 volts

Meets Requirements of:

ESD Protective Packaging Level 3 Technical Requirements

Test Procedures/Method

ANSI/ESD STM11.11 ANSI/ESD STM11.11 ANSI/ESD STM11.31, EIA 541 Modified Incline Plane

Modified Incline Plane

ANSI/EIA-541/Appendix E, 1kV Discharge

Physical Properties

Film Thickness Nominal 3.0 mil (0.07mm) ±10% Width (Inside Dimensions) Nominal -0" / + 0.250"

Length (Inside Dimensions)

Nominal ± 0.125"; Offset 0 to 1/4"

Light Transmission >40% (Tobias)
Heat Seal >10 lbs/in
Tensile Strength 4600 PSI, 32 MPa

Puncture Resistance >10 lbs
Non-corrosive Pass
Silicone Not detected

Marking Adhesion Pass

MIL-STD-3010, 1003

ASTM D-1003 375°F, 1/2 sec 60 psi

ASTM D882 MIL-STD-3010, 2065 MIL-STD-3010, M3005

FTIR

IPC-TM-650 2.4.1

ANSI/ESD S541 Section 6.2 Outside an EPA

"Transportation of sensitive products outside of an EPA shall require packaging that provides:

- 1. Low charge generation
- 2. Dissipative or conductive materials for intimate contact
- 3. A structure that provides electrostatic discharge shielding."

RoHS, REACH, and Conflict Minerals Statement:

See RoHS, REACH, and Conflict Minerals Statement at Desco.com.

Limited Warranty

See Desco's Limited Warranty at Desco.com

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc. See Bag Selection Chart Click HERE.



Made in the United States of America

Specifications and procedures subject to change without notice.

STATSHIELD® BAG, SHIELDING, METAL-IN, 3.0 MIL (0.07mm)

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: <u>Desco.com</u> PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370

DRAWING NUMBER 13405

June 2019

DESCO