

**A-series  
AEP 2C 1.5**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Product image****Spring connection with PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Type       | AEP 2C 1.5                 |
| Order No.  | <a href="#">1552600000</a> |
| Version    | A-series, End plate        |
| GTIN (EAN) | 4050118359602              |
| Qty.       | 50 pc(s).                  |

**A-series  
AEP 2C 1.5**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Width      | 2.1 mm   | Width (inches)  | 0.083 inch |
| Height     | 52.76 mm | Height (inches) | 2.077 inch |
| Depth      | 26.3 mm  | Depth (inches)  | 1.035 inch |
| Net weight | 1.512 g  |                 |            |

**Temperatures**

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature, max.        | 55 °C          | Storage temperature, min.        | -25 °C |
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C         |                                  |        |

**Material data**

|                           |       |        |            |
|---------------------------|-------|--------|------------|
| Material                  | Wemid | Colour | dark beige |
| UL 94 flammability rating | V-0   |        |            |

**System specifications**

|         |           |
|---------|-----------|
| Version | End plate |
|---------|-----------|

**Additional technical data**

|         |     |                   |     |
|---------|-----|-------------------|-----|
| Snap-on | Yes | With snap-in pegs | Yes |
|---------|-----|-------------------|-----|

**Classifications**

|            |             |             |             |
|------------|-------------|-------------|-------------|
| ETIM 6.0   | EC000886    | ETIM 7.0    | EC000886    |
| eClass 9.1 | 27-14-11-33 | eClass 10.0 | 27-14-11-33 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |   |
|--------------------|---|
| Brochure/Catalogue | <a href="#">CAT 1 TERM 16/17 EN</a>             |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>        |
| Engineering Data   | <a href="#">STEP</a>                            |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |