

RAFIX 16 F, signal indicator, flat bezel, round collar, bezel blue



fields of application

- › Measurement-control-regulation
- › Electrical engineering
- › Mechanical and system engineering
- › Vehicle construction

description

RAFIX control components are defined by RAFI as modular elements, including of actuator element, coupling if necessary and individual contact or lighting element.

Actuators (such as pushbuttons, emergency-stop pushbuttons, etc.) have the specified tactility, reset and general function only in combination with the appropriate contact elements.

technical data

› general

| | |
|---|--|
| illuminated | Yes |
| Bezel color | blue |
| Collar color | metallic silver |
| Collar shape | round |
| Operating temperature, min. | -25 °C |
| Operating temperature, max. | 55 °C |
| Storage temperature, min. | -40 °C |
| Storage temperature, max. | 85 °C |
| Packaging | Box |
| Packaging unit | 10 pcs. |
| Environment resistance | IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-33 IEC 60068-2-78 |
| Degree of protection, front side, according to DIN EN 60529 | IP65 |
| RoHS compliant | Yes |
| REACH compliant | Yes |

› mounting diameters

direct links

- › [RAFI eCatalog](#)

| | |
|-----------------------------|---------------|
| Mounting hole | 22.3 mm |
| Mounting depth | 50 mm |
| Installation height | 1.9 mm |
| Grid, min. | 30 x 30 mm |
| Outside dimension, length | 28 mm |
| Outside dimension, width | 28 mm |
| Outside dimension, height | 26.2 mm |
| Collar dimension | ø 28 mm |
| > mechanical data | |
| Fixing | Threaded ring |
| Threaded ring torque, max. | 1.2 Nm |

drawings

Dimensioned drawing