




Nickel Plated Brass w/ PVDF - Strain Relief Fittings PG/NPT/Metric & Elongated Threads



PVDF Spline w/ Viton® Insert: High/Low Temperature & Chemical Resistant

| Part Numbers | | Cable Range Inches (mm) | Thread Type & Size See page 49 for thread specs | Dimensions in Inches (mm) | | | | |
|--|---|-------------------------------------|--|---|---------------------|---------------------------------------|--|--------------------------------------|
| Standard | Elongated | | | A Clearance Hole + .01" (+.25 mm) | B Body Length | D Thread Length Standard | D Thread Length Elongated | F ₁ /F Wrench Flats |
| | | -31 °F to 302 °F (-35 °C to 150 °C) | | | | | | |
|  |  | | | | | | | |
| CD07AA-RV | CD07CA-RV | .12 - .26 (3 - 6.5) | PG 7 / 1/4" NPT | .49 (12.5) | .75 (19) | .20 (5) | .39 (10) | .55 (14) |
| CD07AR-RV | CD07CR-RV | .08 - .20 (2 - 5) | | | | | | |
| CD09AA-RV | CD09CA-RV | .16 - .31 (4 - 8) | PG 9 | .60 (15.2) | .83 (21) | .24 (6) | .39 (10) | .67 (17) |
| CD09AR-RV | CD09CR-RV | .08 - .24 (2 - 6) | | | | | | |
| CD11AA-RV | CD11CA-RV | .20 - .39 (5 - 10) | PG 11 | .73 (18.5) | .87 (22) | .24 (6) | .39 (10) | .79 (20) |
| CD11AR-RV | CD11CR-RV | .12 - .28 (3 - 7) | | | | | | |
| CD13AA-RV | CD13CA-RV | .24 - .47 (6 - 12) | PG 13 / 13.5 | .80 (20.3) | .94 (24) | .26 (6.5) | .39 (10) | .87 (22) |
| CD13AR-RV | CD13CR-RV | .20 - .35 (5 - 9) | | | | | | |
| CD16AA-RV | CD16CA-RV | .39 - .55 (10 - 14) | PG 16 | .89 (22.5) | .91 (23) | .26 (6.5) | .39 (10) | .94 (24) |
| CD16AR-RV | CD16CR-RV | .28 - .47 (7 - 12) | | | | | | |
| CD21AA-RV | CD21CA-RV | .51 - .71 (13 - 18) | PG 21 | 1.12 (28.4) | .94 (24) | .28 (7) | .47 (12) | 1.18 (30) |
| CD21AR-RV | CD21CR-RV | .35 - .63 (9 - 16) | | | | | | |
| CD29AA-RV | CD29CA-RV | .71 - .98 (18 - 25) | PG 29 | 1.47 (37.3) | 1.14 (29) | .31 (8) | .47 (12) | 1.57 (40) |
| CD29AR-RV | CD29CR-RV | .51 - .79 (13 - 20) | | | | | | |
| CD36AA-RV | CD36CA-RV | .87 - 1.26 (22 - 32) | PG 36 | 1.85 (47) | 1.38 (35) | .31 (8) | .59 (15) | 1.97 (50) |
| CD36AR-RV | CD36CR-RV | .79 - 1.02 (20 - 26) | | | | | | |
| CD42AA-RV | CD42CA-RV | 1.26 - 1.50 (32 - 38) | PG 42 | 2.13 (54.1) | 1.46 (37) | .35 (9) | .59 (15) | 2.24 (57) |
| CD42AR-RV | CD42CR-RV | .98 - 1.22 (25 - 31) | | | | | | |
| CD48AA-RV | CD48CA-RV | 1.46 - 1.73 (37 - 44) | PG 48 | 2.34 (59.4) | 1.50 (38) | .39 (10) | .59 (15) | 2.52 (64) |
| CD48AR-RV | CD48CR-RV | 1.14 - 1.38 (29 - 35) | | | | | | |
| CD09NA-RV | - | .16 - .31 (4 - 8) | 3/8" NPT | .68 (17.2) | .83 (21) | .59 (15) | - | .67 (17) / .75 (19) |
| CD09NR-RV | - | .08 - .24 (2 - 6) | | | | | | |
| CD13NA-RV | - | .24 - .47 (6 - 12) | 1/2" NPT | .83 (21.1) | .94 (24) | .51 (13) | - | .87 (22) / .94 (24) |
| CD13NR-RV | - | .20 - .35 (5 - 9) | | | | | | |
| CD21NA-RV | - | .51 - .71 (13 - 18) | 3/4" NPT | 1.05 (26.7) | .98 (25) | .51 (13) | - | 1.18 (30) |
| CD21NR-RV | - | .35 - .63 (9 - 16) | | | | | | |
| CD12MA-RV | CD12DA-RV | .12 - .26 (3 - 6.5) | M12 x 1.5 | .47 (12) | .75 (19) | .26 (6.5) | .39 (10) | .55 (14) |
| CD12MR-RV | CD12DR-RV | .08 - .20 (2 - 5) | | | | | | |
| CD16MA-RV | CD16DA-RV | .16 - .31 (4 - 8) | M16 x 1.5 | .63 (16) | .83 (21) | .24 (6) | .39 (10) | .67 (17) / .75 (19) |
| CD16MR-RV | CD16DR-RV | .08 - .24 (2 - 6) | | | | | | |
| CD17MA-RV | CD17DA-RV | .20 - .39 (5 - 10) | M16 x 1.5 | .63 (16) | .87 (22) | .24 (6) | .39 (10) | .79 (20) |
| CD17MR-RV | CD17DR-RV | .12 - .28 (3 - 7) | | | | | | |
| CD20MA-RV | CD20DA-RV | .24 - .47 (6 - 12) | M20 x 1.5 | .79 (20) | .91 (23) | .24 (6) | .39 (10) | .87 (22) |
| CD20MR-RV | CD20DR-RV | .20 - .35 (5 - 9) | | | | | | |
| CD22MA-RV | CD22DA-RV | .39 - .55 (10 - 14) | M20 x 1.5 | .79 (20) | .94 (24) | .24 (6) | .39 (10) | .94 (24) |
| CD22MR-RV | CD22DR-RV | .28 - .47 (7 - 12) | | | | | | |
| CD25MA-RV | CD25DA-RV | .51 - .71 (13 - 18) | M25 x 1.5 | .98 (25) | 1.02 (26) | .28 (7) | .47 (12) | 1.18 (30) |
| CD25MR-RV | CD25DR-RV | .35 - .63 (9 - 16) | | | | | | |
| CD32MA-RV | CD32DA-RV | .71 - .98 (18 - 25) | M32 x 1.5 | 1.26 (32) | 1.22 (31) | .31 (8) | .47 (12) | 1.57 (40) |
| CD32MR-RV | CD32DR-RV | .51 - .79 (13 - 20) | | | | | | |
| CD40MA-RV | CD40DA-RV | .87 - 1.26 (22 - 32) | M40 x 1.5 | 1.57 (40) | 1.46 (37) | .31 (8) | .59 (15) | 1.97 (50) |
| CD40MR-RV | CD40DR-RV | .79 - 1.02 (20 - 26) | | | | | | |



Suggested Clearance Hole for Non-Threaded Mounting



Viton® and Teflon® is a federally registered trademark of DuPont Dow Elastomer. *Note: VDE Approval only applies to Fittings with Metric Thread.

Dome Fittings also available with the following approvals:



Typical Application:

- High Performance
- Extreme Temperatures
- Sturdy

