

## Specification Sheet

Part Number: 170-03092



Braided Sleeving, Expandable, Flame Retardant, .75" Dia, PET, Black, 250 ft/bulk reel

Article Number	170-03092
Type	BSPFR340B
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.</li><li>• Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.</li></ul>
Quantity Per	reel

### Product Description

A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

**Short Description**

Braided Sleeving, Expandable, Flame Retardant, .75" Dia, PET, Black, 250 ft/bulk reel

**Global Part Name**

BSPFR340B-PET-BK

**Length L (Imperial)**

250.0

**Length L (Metric)**

76.2

**Bundle Diameter Min (Imperial)**

0.5

**Bundle Diameter Min (Metric)**

12.7

**Bundle Diameter Max (Imperial)**

1.25

**Bundle Diameter Max (Metric)**

31.8

**Diameter D (imperial)**

0.75

**Diameter D (metric)**

19.1

**Nominal Diameter (Imperial)**

3/4

**Nominal Diameter (Metric)**

19.1

**Material**

Polyester (PET)

**Material Shortcut**

PET

**Flammability**

UL VW-1 Mil-202 FMVSS 302 FAR 25

**Halogen free** Yes

**Operating Temperature (Metric)** -94°F to +257°F (-70°C to +120°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Certification/Specification WEB** UL 94 VW-1

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** Yes

**Package Quantity(Imperial)** 250

**Package Quantity (Metric)** 76.20

**Customs Number** 3926909987

**Weight (Metric)** 1.0

**Weight (Imperial)** 2.2