

## RAFIX 16, lamp socket W2 x 4.6d, quick-connect terminal, for W 2 x 4.6d



### fields of application

- › Measurement-control-regulation
- › Electrical engineering
- › Mechanical and system engineering
- › Industrial robots

### description

### technical data

#### › general

|  |  |
|--|--|
| illuminated  | Yes  |
| Color  | light gray   |
| Operating temperature, min.                              | -25 °C   |
| Operating temperature, max.                              | 55 °C  |
| Storage temperature, min.                                | -40 °C   |
| Storage temperature, max.                                | 85 °C  |
| Lamp socket  | W 2 x 4.6d   |
| Vibration-resistance according to standard IEC 60068-2-6 | 10 g at 20 - 500 Hz  |
| Shock resistance according to standard IEC 60068-2-27    | 50 g at 11 ms amplitude semi-sinusoidal                              |
| Packaging unit   | 5 pcs.   |
| net weight   | 7.4 g  |
| Environment resistance                                   | IEC 60068-2-14<br>IEC 60068-2-30<br>IEC 60068-2-33<br>IEC 60068-2-78 |
| RoHS compliant   | Yes  |
| REACH compliant  | Yes  |

#### › mounting diameters

|                           |         |
|---------------------------|---------|
| Mounting depth            | 44.7 mm |
| Outside dimension, length | 22.2 mm |

### direct links

- › [RAFI eCatalog](#)

Outside dimension, width 22.2 mm

Outside dimension, height 34.4 mm

> **mechanical data**

Fixing Latching

Terminal on the rear Flat quick-connect terminal 2.8 x 0.8

Lötbarkeit No

**drawings**

---

**System drawing**