

## RAFIX 22 QR, lamp socket, screw terminal, with coupling, for BA9s



### fields of application

- > Measurement-control-regulation
- > Electrical engineering
- > Mechanical and system engineering
- > Vehicle construction



### description

RAFIX control components are defined by RAFI as modular elements, including of actuator element, coupling if necessary and individual contact or lighting element.

Actuators (such as pushbuttons, emergency-stop pushbuttons, etc.) have the specified tactility, reset and general function only in combination with the appropriate contact elements.

### technical data

#### > general

illuminated	Yes
Color	light gray
Operating temperature, min.	-25 °C
Operating temperature, max.	70 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	80 °C
Lamp socket	BA9s
Vibration-resistance according to standard IEC 600068-2-6	10 g at 40 - 500 Hz
Shock resistance according to standard IEC 60068-2-27	50 g at 11 ms amplitude semi-sinusoidal
Packaging unit	10 pcs.
net weight	17.8 g
Environment resistance	IEC 60068-2-14 IEC 60068-2-30

#### direct links

> [RAFI eCatalog](#)

IEC 60068-2-33

IEC 60068-2-78

RoHS compliant Yes

REACH compliant Yes

**> mounting diameters**

Mounting depth 56.4 mm

Outside dimension, length 49.9 mm

Outside dimension, width 39.5 mm

Outside dimension, height 30 mm

**> mechanical data**

Fixing Latching

Terminal on the rear Screw terminal

**> electrical data**

Operating voltage of the luminous element, min. 6 V

Operating voltage of the luminous element, max. 250 V

**drawings**

**System drawing**

