

**VG MS ZE (standard brass cable gland strain relief)
VG 29-MS54-ZE**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Cable gland with external concentric strain relief
(clamping jaws), IP 54

General ordering data

Type	VG 29-MS54-ZE
Order No.	1718860000
Version	VG MS ZE (standard brass cable gland strain relief), Cable glands, PG 29, 8 mm, OD min. 17 - OD max. 27 mm, IP65, Brass, nickel-plated
GTIN (EAN)	4008190352080
Qty.	25 pc(s).

Creation date September 12, 2020 2:19:47 AM CEST

Catalogue status 28.08.2020 / We reserve the right to make technical changes.

**VG MS ZE (standard brass cable gland strain relief)
VG 29-MS54-ZE**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

Length	43 mm	Length (inches)	1.693 inch
Net weight	149.5 g		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General information

Material	Brass, nickel-plated	Cable glands	PG
External thread	PG 29	Length of thread	8 mm
AF size 1	42 mm	AF size 2	40 mm
Protection degree	IP54	Protection degree with GWDR	IP65
Operating temperature range, min.	-20 °C	Operating temperature range, max.	80 °C
Outer cable diameter, min.	17 mm	Outer cable diameter, max.	27 mm
Clamping range, strain relief, min.	19 mm	Clamping range, strain relief, max.	30 mm
Halogen	No	Seal insert	NBR
Torque for cap nut, min.	6.7 Nm	Torque for cap nut, max.	6.7 Nm
Torque for connecting adapter, min.	10 Nm	Torque for connecting adapter, max.	10 Nm

Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
eClass 9.0	27-14-44-32	eClass 9.1	27-14-44-32
eClass 10.0	27-14-44-32	UNSPSC	30-21-18-01

Approvals

Approvals



ROHS Conform

Downloads

Brochure/Catalogue	CAT 3 HDC 17/18 EN CAT 5 ENCL 17/18 EN
Engineering Data	EPLAN_WSCAD