

## PCB terminal block - SPTA 1/ 4-3,5 - 1752120

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, Nominal current: 9 A, Nom. voltage: 200 V, Pitch: 3.5 mm, Number of positions: 4, Connection method: Push-in spring connection, Mounting: Wave soldering, Conductor/PCB connection direction: 65 °, Color: green



The illustration shows the 10-position version

### Product Features

- Compact design with a depth of just 10 mm
- Drilling diagram and dimensions are the same shape as the proven SMKDS 1 screw solution
- Arrangement over several rows possible for high packing densities
- User-friendly and quick conductor connection using Push-in direct plug-in technology
- Easy operation when releasing the conductor via the orange actuating lever
- Different pitches can be combined depending on product range



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 50 pc    |
| Weight per Piece (excluding packing) | 2.04 g   |
| Custom tariff number                 | 85369010 |
| Country of origin                    | Poland   |

### Technical data

#### Dimensions

|                          |              |
|--------------------------|--------------|
| Length                   | 10 mm        |
| Pitch                    | 3.50 mm      |
| Dimension a              | 10.5 mm      |
| Length of the solder pin | 3.5 mm       |
| Pin dimensions           | 0,6 x 1,0 mm |

## PCB terminal block - SPTA 1/ 4-3,5 - 1752120

### Technical data

#### Dimensions

|               |        |
|---------------|--------|
| Pin spacing   | 3.5 mm |
| Hole diameter | 1.1 mm |

#### General

|  |                   |
|--|-------------------|
| Range of articles                      | SPTA 1/           |
| Insulating material group              | I                 |
| Rated surge voltage (III/3)            | 2.5 kV            |
| Rated surge voltage (III/2)            | 2.5 kV            |
| Rated surge voltage (II/2)             | 2.5 kV            |
| Rated voltage (III/3)                  | 160 V             |
| Rated voltage (III/2)                  | 200 V             |
| Rated voltage (II/2)                   | 400 V             |
| Connection in acc. with standard       | EN-VDE            |
| Nominal current $I_N$                  | 9 A               |
| Nominal cross section                  | 1 mm <sup>2</sup> |
| Maximum load current                   | 9 A               |
| Insulating material                    | PA                |
| Solder pin surface                     | Sn                |
| Flammability rating according to UL 94 | V0                |
| Stripping length                       | 8 mm              |
| Number of positions                    | 4                 |

#### Connection data

|  |                      |
|--|----------------------|
| Conductor cross section solid min.   | 0.2 mm <sup>2</sup>  |
| Conductor cross section solid max.   | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible min.                                      | 0.2 mm <sup>2</sup>  |
| Conductor cross section flexible max.                                      | 1 mm <sup>2</sup>    |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 0.75 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 0.75 mm <sup>2</sup> |
| Conductor cross section AWG min.   | 24                   |
| Conductor cross section AWG max.   | 16                   |

#### Standards and Regulations

|  |        |
|--|--------|
| Connection in acc. with standard       | EN-VDE |
|  | CUL    |
| Flammability rating according to UL 94 | V0     |

# PCB terminal block - SPTA 1/ 4-3,5 - 1752120

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141109 |
| eCl@ss 4.1 | 27141109 |
| eCl@ss 5.0 | 27141190 |
| eCl@ss 5.1 | 27141190 |
| eCl@ss 6.0 | 27261101 |
| eCl@ss 7.0 | 27440401 |
| eCl@ss 8.0 | 27440401 |
| eCl@ss 9.0 | 27440401 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002643 |
| ETIM 5.0 | EC002643 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211801 |
| UNSPSC 7.0901 | 39121432 |
| UNSPSC 11     | 39121432 |
| UNSPSC 12.01  | 39121432 |
| UNSPSC 13.2   | 39121432 |

## Approvals

### Approvals

---

#### Approvals

UL Recognized / VDE Gutachten mit Fertigungsüberwachung / cUL Recognized / CCA / IECCEB CB Scheme / EAC / EAC / cULus Recognized

---

#### Ex Approvals

---


#### Approvals submitted

---


#### Approval details

# PCB terminal block - SPTA 1/ 4-3,5 - 1752120


## Approvals

UL Recognized 

|                                | B     | D     |
|--------------------------------|-------|-------|
| mm <sup>2</sup> /AWG/kcmil     | 26-16 | 26-16 |
| Nominal current I <sub>N</sub> | 10 A  | 10 A  |
| Nominal voltage U <sub>N</sub> | 150 V | 300 V |


VDE Gutachten mit Fertigungsüberwachung 

| mm <sup>2</sup> /AWG/kcmil     | 0.2-1.5 |
|--------------------------------|---------|
| Nominal current I <sub>N</sub> | 9 A     |
| Nominal voltage U <sub>N</sub> | 130 V   |

cUL Recognized 


|                                | B     | D     |
|--------------------------------|-------|-------|
| mm <sup>2</sup> /AWG/kcmil     | 26-16 | 26-16 |
| Nominal current I <sub>N</sub> | 10 A  | 10 A  |
| Nominal voltage U <sub>N</sub> | 150 V | 300 V |

CCA

IECEE CB Scheme 

EAC


EAC

cULus Recognized 

# PCB terminal block - SPTA 1/ 4-3,5 - 1752120

## Drawings

Drilling diagram



Dimensional drawing

