



Accessories - FL 3-V - 1760336

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, Pitch: 2.5 mm, Number of positions: 3, Connection method: Slip-on connection, Mounting: Wave soldering, Color: green



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 017918 030872
Weight per Piece (excluding packing)	4.93 g
Custom tariff number	85369010
Country of origin	Poland

Technical data

Dimensions

Pitch	2.50 mm
Constructional height	13.3 mm
Height	18.3 mm
Pin dimensions	0,8 x 1,0 mm
Pin spacing	5 mm
Hole diameter	1.3 mm

General

Range of articles	FL
Nominal cross section	0 mm ²
Insulating material	PA 6.6
Solder pin surface	Sn
Flammability rating according to UL 94	V2
Number of positions	3

Standards and Regulations

Connection in acc. with standard	CSA
----------------------------------	-----

Accessories - FL 3-V - 1760336

Technical data

Standards and Regulations

Flammability rating according to UL 94	V2
--	----

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440490
eCl@ss 8.0	27440402
eCl@ss 9.0	27440402

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002498
ETIM 5.0	EC002637

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

CSA / EAC / EAC / cULus Recognized / cULus Recognized


Ex Approvals

Approvals submitted

Accessories - FL 3-V - 1760336

Approvals


Approval details

CSA 	
Nominal current IN	10 A
Nominal voltage UN	300 V

EAC

EAC

cULus Recognized	
Nominal current IN	10 A
Nominal voltage UN	300 V

cULus Recognized 
--