

**Product:** <u>1813A</u> ☑



# Audio Cable, 2 Conductor 24 AWG, BC

# **Product Description**

Audio Cable, CM-Rated, 1-24 AWG stranded high-conductivity bare copper pair with PVC insulation, +90% bare copper spiral shield, PVC jacket

# **Technical Specifications**

# **Physical Characteristics (Overall)**

Conductor					
AWG	Stranding	Material		Nominal Diameter	No. of Pairs
24	27x38	BC - Bare Copper (High Conductivity)		0.0246 in	1
Conductor Count:		2			
Total N	Number of Pa	Pairs: 1			

### Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.059 in	0.017 in

### **Color Chart**

Number	Color
1	Blue & Red

### Outer Shield Material

Туре	Material	Coverage [%]
Spiral Serve / Screen	Bare Copper (BC)	90%

# Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.236 in	0.055 in

# **Electrical Characteristics**

## Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Outer Shield DCR
22.8 Ohm/1000ft	22.8 Ohm/1000ft	11.6 Ohm/1000ft

### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
33 pF/ft	61 pF/ft

#### Inductance

Nominal Inductance

# Voltage

Non-UL Voltage Rating 100 V RMS

### **Temperature Range**

Operating Temp Range:	-30°C To +60°C

### **Mechanical Characteristics**

Bulk Cable Weight:	30 lbs/1000ft
Max. Pull Tension:	10 lbs
Min Bend Radius/Minor Axis:	2.5 in

### **Applicable Environmental and Other Programs**

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

### Suitability

Suitability - Indoor:	Yes

### Plenum/Non-Plenum

Plenum (Y/N): No	

### **Part Number**

### Variants

Item #	Color	Putup Type	Length	UPC
1813A B59328	Black, Matte	Reel	328 ft	612825123408
1813A B591000	Black, Matte	Reel	1,000 ff	612825123392
Footnote:			C-	CRATE REEL PL

### **History**

Update and Revision:	Revision Number: 0.272 Revision Date: 06-24-2020

# © 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.