

**Cabtite**  
**CABTITE KEL 24/10**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Cabtite enables you to feed pre-assembled lines through the electrical cabinet wall while maintaining IP54-level protection. As the cable does not have to be split, the manufacturer's guarantee is not invalidated.

**General ordering data**

Type	CABTITE KEL 24/10
Order No.	<a href="#">1827760000</a>
Version	Cable entry strips, Cabtite, Plastic, Black, Height: 58 mm, Width: 147 mm, Depth: 17 mm, -40 °C - 140 °C
GTIN (EAN)	4032248333080
Qty.	10 pc(s).

## Data sheet

### Cabtite CABTITE KEL 24/10

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Width	147 mm	Width (inches)	5.787 inch
Height	58 mm	Height (inches)	2.283 inch
Depth	17 mm	Depth (inches)	0.669 inch
Net weight	112 g		

### General information

Material	Plastic	Operating temperature range, max.	140 °C
Operating temperature range, min.	-40 °C		

### Classifications

ETIM 3.0	EC000441	ETIM 4.0	EC000441
ETIM 5.0	EC000441	ETIM 6.0	EC002624
UNSPSC	30-21-18-01	eClass 5.1	27-14-92-01
eClass 6.2	27-14-92-01	eClass 7.1	27-14-92-01
eClass 8.1	27-14-92-01	eClass 9.0	27-14-44-38
eClass 9.1	27-18-92-65		

### Approvals

ROHS	Conform
------	---------

### Downloads

Brochure/Catalogue	<a href="#">CAT 5 ENCL 17/18 EN</a>
Engineering Data	<a href="#">EPLAN.WSCAD</a>