

HDC KT ...

Cable grommets, small



Technical data

Material, gray	free from elastomers, halogens and silicone
Material, black	elastomers with very high chemical resistance
Temperature range	-20°C ... 80°C
UL 94 flammability rating	V0

Ordering data


Type	Clamping range [mm]	Qty.	Order No. gray	Order No. black
HDC KT 5	5-6	10	1826480000	1827810000
HDC KT 6	6-7	10	1826490000	1827830000
HDC KT 7	7-8	10	1826500000	1827840000
HDC KT 8	8-9	10	1826510000	1827850000
Blanking plugs, small				
HDC BTK		10	1828170000	1828200000

KVT 32

KVT 32 and locknut for D-Sub 9



KVT 32



Locknut for D-Sub 9
KGM-SUB-D9

Technical data

Material	Polyamide, free from halogens and silicone
Class of protection	IP54, when the correct cable grommet is selected
Temperature range	-5 °C ... 70 °C
UL 94 flammability rating	V0

Ordering data

Type	Thread	For grommet small large	Qty.	Order No. white	Order No. black
HDC KVT 32	M 32 x 1.5	1 -	10	1826670000	1828270000
Locknut for D-Sub 9					
KGM-SUB-D9	M 32 x 1.5		10	1828250000	1828300000

Note: Please refer to catalog 5 for the complete range.

HDC KEL 16

Cable entry strip

KEL 16/8 with 8 small grommets



KEL 16/4 with closed half-shell for 4 small grommets



Snap frame
KEL 16 SNAP



Technical data

Material	Polyamide, halogenfree, siliconfree
Color	black
Temperature range	-20°C ... 80°C
Ingress protection class	IP 54, when correct cable grommet is used
UL 94 flammability rating	V0

Ordering data

Type	No. of grommet positions small large	Qty.	Order No. black
HDC KEL 16/8	8 -	10	1825910000
HDC KEL 16/4	4 -	10	1825900000
Blanking plugs, small			
HDC KEL 16 SNAP		10	1827770000