
# **Detailed Specifications & Technical Data**

## **ENGLISH MEASUREMENT VERSION**



19352 Portable Cordage - UL/CSA Types: SJT



For more Information please call

1-800-Belden1



## **General Description:**

SJT PVC jacket, 300V, 60°C, paper tape separator, smooth jacket, UL/CSA listed, international color code: light blue, brown, green/yellow.

Physical Characteristics (Overall)				
Conductor AWG:				
# Conductors AWG Stranding Conductor Material 3   18   42x34   BC - Bare Copper				
Total Number of Conductors:	3			
Type of Cordage:	SJT			
Insulation Insulation Material:				
Insulation Material Wall Thickness (in.) PVC - Polyvinyl Chloride .032				
Outer Shield Outer Shield Material: Outer Shield Material Unshielded				
Outer Jacket Outer Jacket Material:  Outer Jacket Material  PVC - Polyvinyl Chloride  .046				
Overall Cable				
Overall Cabling Fillers: Overall Cabling Color Code Chart:	Paper			
Color Light Blue Brown Green/Yellow				
Overall Nominal Diameter:	0.328 in.			
Mechanical Characteristics (Overall)				
UL Temperature Rating:	60°C			
Bulk Cable Weight:	64 lbs/1000 ft.			
Applicable Specifications and Agency Compliance (Overall)				
Applicable Standards & Environmental Programs				
NEC/(UL) Specification:	SJT			
CSA Specification:	SJT			
EU Directive 2011/65/EU (ROHS II):	Yes			
EU CE Mark:	Yes			
EU Directive 2000/53/EC (ELV):	Yes			
EU Directive 2002/95/EC (RoHS):	Yes			
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004			
EU Directive 2002/96/EC (WEEE):	Yes			
EU Directive 2003/11/EC (BFR):	Yes			
CA Prop 65 (CJ for Wire & Cable):	Yes			
MII Order #39 (China RoHS):	Yes			

Page 1 of 2 01-05-2017

# **Detailed Specifications & Technical Data**

### **ENGLISH MEASUREMENT VERSION**



# 19352 Portable Cordage - UL/CSA Types: SJT

Plenum/Non-Plenum Plenum (Y/N): No

**Surface Printing (Overall)** 

**Electrical Characteristics (Overall)** 

Max. Operating Voltage - UL:

Voltage 300 V RMS

Max. Recommended Current:

Current 10 Amps per conductor @ 25°C 7 Amps per conductor @ 25°C over 50 ft.

Dielectric Withstand Voltage:

1500 V AC Applied For 1 Min

#### **Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
19352 010250	250 FT	17.500 LB	BLACK	С	3#18 PVC PVC SJT

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 07-30-2009

© 2017 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its bublication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

Page 2 of 2