



HARNESSING

HEAT SHRINK BOOTS



✓ Active

TE CONNECTIVITY (TE)

202D142-12-60-0

Raychem | CAP , CRPS

202D142-12-60-0

TE Internal Number: 811542-000

Alias ID: 5-1196311-8

[EU RoHS Compliant](#)

[EU ELV Compliant](#)

Lipped Yes

Operating Temperature Range (°C) -55 – 200

Fluid/Chemical Resistance Suitable for long term fluid immersion & elevated temperatures including fuel

Adhesive Options S1125 Separate Adhesive, -75°C – 150°C (-103°F – 302°F), S1255-04 Separate Adhesive, -55°C – 200°C (-67°F – 392°F)

Material Systems Code 200

[↓ PRODUCT DRAWING](#)
English

DOCUMENTATION

Product Drawings

Boot, Straight, With Lip

PDF

English

Boot, Straight, With Lips

PDF

English

Product Specifications

Product Specification

Raychem Fluoro Elastomer Molded Components Flame-Retarded, Flexible, Heat-Shrinkable

PDF

English

Product Environmental Compliance

Safety Data Sheet

Heat-Shrinkable Fluoropolymer Products

PDF

English

Heat-Shrinkable Fluoropolymer Products

PDF

German

Heat-Shrinkable Fluoropolymer Products

PDF

French

Heat-Shrinkable Fluoropolymer Products

PDF

Dutch

Heat-Shrinkable Fluoropolymer Products

PDF

Italian

Heat-Shrinkable Fluoropolymer Products

PDF

Spanish

Heat-Shrinkable Fluoropolymer Products

PDF

Swedish

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Molded Part Type Molded Boot

Configuration Features

Lipped Yes

Body Features

Material Systems Code 200

Adhesive Pre-Coat No

Entry Size (Braided or Magneform Adapter) 10, 11

Entry Size (Solid or Fixed Adapter) 6 – 8

Material Modified Fluoro-Elastomer

Entry Size (Tinel-Lock Adapter) 10, 7, 8

Entry Size (Spin Coupling Adapter) 8 – 14

Dimensions

Cable Diameter Range 7.1 – 16 mm [.28 – .63 in]

Wire/Cable Outside Diameter .3 in, .31 in, .35 in, .39 in, .43 in, .433 in, 10 mm, 11 mm, 8 mm, 9 mm

Usage Conditions

Operating Temperature Range (°C) -55 – 200

Operation/Application

Power Cable Accessory No

Industry Standards

Government Qualified No

Approved Standards BS-G-198-5-DD, DEF Std 59-97 Issue 3 Type DD, SAE AS I 81765/4

Other

Fluid/Chemical Resistance Suitable for long term fluid immersion & elevated temperatures including fuel

Adhesive Options S1125 Separate Adhesive, -75°C – 150°C (-103°F – 302°F), S1255-04 Separate Adhesive, -55°C – 200°C (-67°F – 392°F)

Adhesive Type Adhesive Purchased Separately

Statement of Compliance

Statement of Compliance

PDF