
Add to basket



19" complete chassis from aluminium, plain top cover and base plate



Photo shows 1 U




Features:

- Complete chassis from aluminium
- Detachable rear panel for easy machining
- EMC shielding of approx. 30 dB(A) at 1 GHz (without additional shielding material)
- In accordance with standard IEC 60297-3-100, -101, -105







h = clear height (overall) (H -8.1 mm) b = clear installation width = 403 mm

Technical information:

Description	Height	Height H	Depth T
Solid top cover and base plate	4 U	177 mm	460 mm

Downloads:

3D PDF with CAD data (STEP/DWG/DXF/PDF) (**Log in** Required) User manual (**Log in** Required)



To gain access to the additional information you must Log in. If you do not yet have a user name, you may Register here.

Delivery comprises: Kit

Item	Qty	Description
1	1	Front panel, Al extrusion, 3 mm; front and rear side of front panels clear passivated
2	1	Rear panel, Al, 2 mm, etched
3	1	Base plate, plain, Al, 1 mm
4	1	Cover plate, plain, Al, 1 mm
5	2	Side panel, Al extrusion, raw; with grooves for threaded insert (2 × 7)
6	1	Assembly kit

Accessories:

Part no.	Description	
20860-259	Front handles incl. assembly kit for 4 U, Al extrusion, anodised, PU 2 pieces	Add to basket

1 of 2 13/12/2010 13:37

2 of 2