Thomas&Betts





210217

UPC Number: 78621086771

Status: Active

Description:

Insulation Piercing Magnet Wire Ring Terminal, Length 1.22 Inches, Width .41 Inches, Length of Teeth .56 Inches, Width of Teeth .38 Inches, Stud Size 10, Wire Range #14 AWG - #10 AWG 4,110 Circular Mil Area -20,760 Circular Mil Area, Copper Alloy, Tin Plated


Features

Designed to penetrate magnet wire insulation during application, eliminating the need for stripping, brazing, welding or other methods of joining magnet wire.

Application

For aluminum to copper, aluminum to aluminum or

	For aluminum to copper, aluminum to aluminum or
	copper to copper magnet wire connections.
General	
Material	Copper
Finish	Tin Plated
Stud Size	10
Dimension Information	
E* (inches)	.17
A (inches)	.38
B (inches)	.56
C (inches)	1.22
D (inches)	.41
Specifications	
Circular Mil Area	4,110 - 20,760
Rectangular Wire Range Thickness (inches)	0809
Rectangular Wire Range Width (inches)	.0818
Round Wire Range AWG	14(a) - 10
Tooling	
Hydraulic Tooling	13100A, 13400, 13642M, TBM15I
Connector & Tooling Chart	Available on Website
Packaging	
T&B Order Multiple	250
T&B Inner Pack	250
Package in Units	1000
T&B Sold in UOM	Each
T&B Weight Per UOM	1.19 lbs. per 100
Application Support	
Product Selector	DT_prod_selector_ringterm
T&B Instruction Sheets	ta00193-tb2
Overview	Available on Website
Notes	
*Note	Reference dimension (crimped height). See installing die illustration for gauging.
**Note	





Not recommended for aluminum magnet wire finer than 21 gauge or 0.4 mm². (a) Four wires max. (b) Six wires max. (c) Six wires max. each barrel (d) Conductors heavier than 6 AWG or 13 mm² require special dies. Contact Thomas & Betts for assistance. (e) Crimping dies may not bottom. Connector height will depend on number and size of wires in barrel. Pump must deliver 9800 psi minimum.

Wire sizes and combinations shown have been tested to and meet or exceed Thomas & Betts specifications. Connectors may be suitable for other wire sizes or combinations. Thomas & Betts sells these connectors with the understanding that the user will perform necessary tests to determine their suitability for the intended purpose.

Certifications

RoHS Compliance

Yes

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com