

## M23\_8P FE,int-thread,STR PUR cable,5M



Image is for illustration purposes only. Please refer to product description.

Part number	21 37 380 0G78 050
Specification	M23_8P FE,int-thread,STR PUR cable,5M
HARTING eCatalogue	<a href="https://b2b.harting.com/21373800G78050">https://b2b.harting.com/21373800G78050</a>

### Identification

Category	System cabling
Series	Circular connectors M23
Identification	Hybrid
Element	Cable assemblies
Specification	Pre-assembled on one side
Connector 1	M23 Male Straight
Type of cable	Copper cable (round)
Features	Flame retardancy Oil and UV resistant Highly EMC resistant

### Version

Cable length	5 m
Number of cores	8
Core structure	4x AWG 16 + 4x AWG 19

### Technical characteristics

Rated current (signal)	10 A
Rated voltage (signal)	250 V
Rated current (power)	40 A
Rated voltage (power)	630 V
Limiting temperature	-40 ... +80 °C



**Pushing Performance**  
Since 1945

## Technical characteristics

Degree of protection acc. to IEC 60529 IP67

---

## Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (cable)	PVC
Colour (cable)	Orange
Material (overmoulding)	Thermoplastic polyurethane (TPU)
Colour (overmoulding)	Black

---

## Commercial data

Packaging size	1
Net weight	1,273 g
Country of origin	China
European customs tariff number	85444290
eCl@ss	27060311 Assembled sensor actuator-line